

# Appendices

## Appendix A Traffic Volumes



15th Ave N

Weekday

15th Ave & CSAH 9

Existing (2024)

Date collected: 7/2/2024

Date printed: 8/9/2024

Time	NB Approach						SB Approach						EB Approach						WB Approach						Int Total	Truck % by Hour
	NB Utm	NB Left	NB Thru	NB Right	South Approach Peds	South Approach Bikes	SB Utm	SB Left	SB Thru	SB Right	North Approach Peds	North Approach Bikes	EB Utm	EB Left	EB Thru	EB Right	West Approach Peds	West Approach Bikes	WB Utm	WB Left	WB Thru	WB Right	East Approach Peds	East Approach Bikes		
	NBU	NBL	NBT	NBR	EB-WB	EB-WB	SBU	SBL	SBT	SBR	EB-WB	EB-WB	EBU	EBL	EBT	EBR	NB-SB	NB-SB	WBU	WBL	WBT	WBR	NB-SB	NB-SB		
0:00	0	4	1	0	0	0	0	0	1	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	7	0%
1:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	1	0%
2:00	0	3	0	0	0	0	0	0	2	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	6	0%
3:00	0	2	2	0	0	0	0	0	1	0	0	0	0	0	1	2	0	0	0	0	0	0	0	0	8	0%
4:00	0	8	5	0	0	0	0	0	0	1	0	0	0	0	0	4	0	0	0	0	0	0	0	0	18	0%
5:00	0	13	8	0	0	0	0	0	10	0	0	0	0	0	1	2	0	0	0	0	1	0	0	0	35	6%
6:00	0	32	16	0	0	0	0	0	11	1	0	0	0	0	1	9	0	0	0	1	7	0	0	0	78	0%
7:00	0	69	26	0	1	0	0	1	26	3	0	0	0	1	10	19	0	0	0	3	15	2	0	0	176	2%
8:00	0	27	19	1	0	0	0	1	17	1	0	0	0	0	4	24	0	0	0	0	9	0	0	0	103	11%
9:00	0	16	14	0	0	0	0	0	25	1	0	0	0	0	11	21	0	0	0	0	8	1	0	0	97	13%
10:00	0	14	18	0	0	0	0	1	13	2	0	0	0	0	7	25	0	0	0	0	6	0	0	0	86	14%
11:00	0	14	16	0	0	0	0	0	16	1	0	0	0	3	6	22	0	0	0	2	4	0	0	0	84	11%
12:00	0	23	25	1	0	0	0	0	28	2	0	0	0	0	4	29	0	0	0	0	3	0	0	0	115	10%
13:00	0	10	20	1	0	0	0	0	19	1	0	0	2	2	9	16	0	0	0	0	4	1	0	0	85	11%
14:00	1	11	26	0	0	0	0	0	27	3	0	0	0	0	8	27	0	0	0	1	7	1	1	0	113	6%
15:00	1	16	24	3	0	0	0	1	21	3	0	0	0	7	12	37	0	0	0	2	6	1	0	0	134	7%
16:00	0	24	41	1	0	0	0	2	34	2	0	0	1	4	25	63	1	0	0	1	9	0	0	0	208	5%
17:00	0	32	37	1	0	0	0	2	38	2	0	0	0	5	17	80	0	0	0	1	12	0	0	0	227	1%
18:00	1	38	21	0	0	0	0	2	19	1	0	0	0	3	9	33	0	0	0	0	5	1	0	0	133	3%
19:00	0	16	22	0	0	0	0	0	14	0	0	0	0	5	6	27	0	0	0	0	5	2	0	0	97	0%
20:00	0	15	14	1	0	0	0	0	22	2	0	0	0	3	9	29	0	0	0	0	2	0	0	0	97	0%
21:00	0	9	15	0	0	0	0	0	9	0	0	0	0	0	5	19	0	0	0	0	0	0	0	0	57	0%
22:00	0	5	8	0	0	0	0	1	7	1	0	0	0	0	2	22	0	0	0	0	0	0	0	0	46	0%
23:00	0	1	0	1	0	0	0	0	0	2	0	0	0	2	0	6	0	0	0	0	0	0	0	0	12	0%
Total	3	402	378	10	1	0	0	11	360	29	0	0	3	35	147	519	1	0	0	11	103	9	1	0	2023	
Approach Total	794						400						705						124							
Truck % By Approach	6%						13%						1%						2%							
Right Turn %	1%						7%						74%						7%							
	NB Utm	NB Left	NB Thru	NB Right	South Approach Peds	South Approach Bikes	SB Utm	SB Left	SB Thru	SB Right	North Approach Peds	North Approach Bikes	EB Utm	EB Left	EB Thru	EB Right	West Approach Peds	West Approach Bikes	WB Utm	WB Left	WB Thru	WB Right	East Approach Peds	East Approach Bikes	Peak Start	PHF
AM Peak	0	69	26	0	1	0	0	1	26	3	0	0	0	1	10	19	0	0	0	3	15	2	0	0	7:00:00 AM	0.86
MD Peak	0	23	25	1	0	0	0	0	28	2	0	0	0	0	4	29	0	0	0	0	3	0	0	0	12:00:00 PM	0.87
PM Peak	0	28	39	1	0	0	0	2	45	2	0	0	0	3	30	72	1	0	0	2	13	0	0	0	4:15:00 PM	0.88



15th Ave N

Weekday

15th Ave & 50th St

Existing (2024)

Date collected: 7/2/2024

Date printed: 8/9/2024

Time	NB Approach						SB Approach						EB Approach						WB Approach						Int Total	Truck % by Hour
	NB Utm	NB Left	NB Thru	NB Right	South Approach Peds	South Approach Bikes	SB Utm	SB Left	SB Thru	SB Right	North Approach Peds	North Approach Bikes	EB Utm	EB Left	EB Thru	EB Right	West Approach Peds	West Approach Bikes	WB Utm	WB Left	WB Thru	WB Right	East Approach Peds	East Approach Bikes		
	NBU	NBL	NBT	NBR	EB-WB	EB-WB	SBU	SBL	SBT	SBR	EB-WB	EB-WB	EBU	EBL	EBT	EBR	NB-SB	NB-SB	WBU	WBL	WBT	WBR	NB-SB	NB-SB		
0:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0%
1:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0%
2:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0%
3:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0%
4:00	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0%
5:00	0	1	4	0	0	0	0	0	2	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0%
6:00	0	7	3	0	0	0	0	0	1	0	0	0	0	0	1	0	0	0	0	0	1	0	0	0	0	0%
7:00	0	11	4	0	0	0	0	0	4	0	0	0	0	0	3	9	0	0	0	1	1	0	0	0	0	0%
8:00	0	11	1	0	0	0	0	0	1	0	0	0	0	0	2	4	0	0	0	0	1	0	0	0	0	10%
9:00	0	7	0	0	0	0	0	0	0	0	0	0	0	0	3	8	0	0	0	1	0	0	0	0	0	0%
10:00	1	3	3	2	0	0	0	0	1	0	0	0	0	0	3	5	0	0	0	1	2	0	0	0	0	0%
11:00	0	6	0	0	0	0	0	0	1	0	0	0	0	0	0	5	0	0	0	0	1	0	0	0	0	8%
12:00	0	1	1	0	0	0	0	0	0	1	0	0	0	0	2	4	0	0	0	0	1	1	0	0	0	9%
13:00	0	4	1	1	0	0	0	0	3	0	0	0	0	0	1	9	0	0	0	0	1	0	0	0	0	0%
14:00	0	8	2	0	0	0	0	0	3	0	0	0	0	0	0	8	0	0	0	0	0	0	0	0	0	0%
15:00	1	7	4	0	0	0	0	0	7	1	0	0	0	0	3	11	0	0	0	0	0	0	1	0	0	0%
16:00	0	11	2	0	0	0	0	0	7	0	0	0	0	0	2	25	0	0	0	2	1	0	1	0	0	0%
17:00	0	9	4	1	0	0	0	0	7	0	0	0	0	0	3	18	1	0	0	3	2	0	0	0	0	0%
18:00	0	6	3	0	0	0	0	0	6	0	0	0	0	0	3	8	0	0	0	1	0	0	1	0	0	7%
19:00	0	7	3	0	0	0	0	0	5	0	0	0	0	0	0	6	0	0	0	1	0	0	0	0	0	0%
20:00	2	2	1	0	0	0	0	0	1	0	0	0	0	0	2	8	0	0	0	0	0	0	0	0	0	0%
21:00	0	0	2	0	0	0	0	0	0	0	0	0	0	0	0	5	0	0	0	0	0	0	0	0	0	0%
22:00	0	0	0	2	0	0	0	0	2	0	0	0	0	0	1	2	0	0	0	1	0	0	0	0	0	0%
23:00	0	2	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0%
Total	4	104	38	6	0	0	0	0	52	2	0	0	0	0	30	136	1	0	0	11	11	1	3	0	399	

Approach Total	152					54							167						26					
Truck % By Approach	1%					0%							3%						0%					
Right Turn %		4%					4%						82%							4%				

	NB Utm	NB Left	NB Thru	NB Right	South Approach Peds	South Approach Bikes	SB Utm	SB Left	SB Thru	SB Right	North Approach Peds	North Approach Bikes	EB Utm	EB Left	EB Thru	EB Right	West Approach Peds	West Approach Bikes	WB Utm	WB Left	WB Thru	WB Right	East Approach Peds	East Approach Bikes	Peak Start	PHF
AM Peak	0	10	6	0	0	0	0	0	3	0	0	0	0	0	4	9	0	0	0	0	1	0	0	0	6:45:00 AM	0.83
MD Peak	0	7	3	0	0	0	0	0	1	0	0	0	0	0	2	8	0	0	0	0	0	0	0	0	9:30:00 AM	0.53
PM Peak	0	13	5	0	0	0	0	0	9	0	0	0	0	0	1	30	0	0	0	4	3	0	0	0	4:15:00 PM	0.90



15th Ave N

Weekday

15th Ave & 60th St

Future (2045)

Date collected: 7/2/2024

Date printed: 8/9/2024

	NB Approach						SB Approach						EB Approach						WB Approach								
Time	NB Utrn	NB Left	NB Thru	NB Right	South Approach Peds	South Approach Bikes	SB Utrn	SB Left	SB Thru	SB Right	North Approach Peds	North Approach Bikes	EB Utrn	EB Left	EB Thru	EB Right	West Approach Peds	West Approach Bikes	WB Utrn	WB Left	WB Thru	WB Right	East Approach Peds	East Approach Bikes	Int Total	Truck % by Hour	
	NBU	NBL	NBT	NBR	EB-WB	EB-WB	SBU	SBL	SBT	SBR	EB-WB	EB-WB	EBU	EBL	EBT	EBR	NB-SB	NB-SB	WBU	WBL	WBT	WBR	NB-SB	NB-SB			
0:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0%	
1:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0%	
2:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0%	
3:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0%	
4:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0%	
5:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	1	0%
6:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2	0	0	0	0	0	0	1	0	0	0	3	0%
7:00	0	0	1	0	0	0	0	0	0	0	0	0	0	0	2	1	0	0	0	0	0	1	0	0	0	5	20%
8:00	0	0	0	0	0	0	0	0	1	0	0	0	0	0	1	0	0	0	0	0	0	1	0	0	0	3	33%
9:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	2	0	0	0	0	0	1	1	0	0	5	0%
10:00	0	0	0	0	0	0	0	0	0	2	0	0	0	2	1	1	0	0	0	0	0	1	0	0	0	7	0%
11:00	0	0	1	0	0	0	0	0	1	0	0	0	0	0	1	0	0	0	0	0	0	1	0	0	0	4	0%
12:00	0	0	0	0	0	0	1	0	0	1	0	0	0	0	2	0	0	0	0	0	0	1	0	0	0	5	40%
13:00	0	0	0	0	0	0	1	1	1	0	0	0	0	0	2	0	0	0	0	0	0	1	2	0	0	8	25%
14:00	0	0	1	0	0	0	0	0	2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	3	0%
15:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2	0	0	0	0	0	0	0	1	0	0	3	33%
16:00	0	2	0	0	0	0	0	0	1	0	0	0	0	0	4	0	0	0	0	0	0	1	1	0	0	9	13%
17:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4	0	0	0	0	0	0	7	0	0	0	11	0%
18:00	0	0	0	0	0	0	0	0	1	0	0	0	0	0	4	0	0	0	0	0	0	1	0	0	0	6	40%
19:00	0	0	1	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2	0%
20:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2	0	0	0	0	0	0	0	0	0	0	2	0%
21:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0%
22:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2	0	0	0	0	0	0	1	0	0	0	3	0%
23:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0%
Total	0	2	4	0	0	0	2	1	7	4	0	0	0	2	31	4	0	0	0	0	0	18	5	0	0	80	

Approach Total

6

14

37

23

Forecasted Approach ADT

20

30

60

60

Existing Approach ADT

20

30

50

60

% Change in ADT (annual)

0.00%

0.00%

0.87%

0.00%

Truck % By Approach

0%

14%

11%

17%

Right Turn %

0%

29%

11%

22%

	NB Utrn	NB Left	NB Thru	NB Right	South Approach Peds	South Approach Bikes	SB Utrn	SB Left	SB Thru	SB Right	North Approach Peds	North Approach Bikes	EB Utrn	EB Left	EB Thru	EB Right	West Approach Peds	West Approach Bikes	WB Utrn	WB Left	WB Thru	WB Right	East Approach Peds	East Approach Bikes	Peak Start	PHF
AM Peak	0	0	1	0	0	0	0	0	0	0	0	0	0	0	4	1	0	0	0	0	1	0	0	0	6:45:00 AM	0.75
MD Peak	0	0	1	0	0	0	0	0	0	2	0	0	0	2	2	1	0	0	0	0	2	0	0	0	#####	0.50
PM Peak	0	0	1	0	0	0	0	0	0	2	0	0	0	2	2	1	0	0	0	0	2	0	0	0	4:15:00 PM	0.50



Weekday

**Existing (2024)**

Date printed: 8/9/2024

Right Turn %	1%
--------------	----

	NB Utm	NB Left	NB Thru	NB Right	South Approach Peds	South Approach Bikes	SB Utm	SB Left	SB Thru	SB Right	North Approach Peds	North Approach Bikes	EB Utm	EB Left	EB Thru	EB Right	West Approach Peds	West Approach Bikes	WB Utm	WB Left	WB Thru	WB Right	East Approach Peds	East Approach Bikes	Peak Start	PHF
AM Peak	0	0	59	0	0	0	0	0	122	0	0	0	0	0	0	2	0	0	0	1	0	0	0	0	7:15:00 AM	0.92
MD Peak	0	2	72	0	0	0	0	0	83	0	0	0	0	1	1	1	0	0	0	0	0	0	0	0	1:15:00 PM	0.87
PM Peak	0	6	87	0	0	0	0	0	120	0	0	0	0	0	0	2	0	0	0	0	0	0	0	0	5:00:00 PM	0.81



# Appendix B

## Traffic Operations Results



Vistro File: K:\...\15th Ave Vistro.vistro

Report File: K:\...\Existing AM.pdf

Scenario 1 Existing AM

7/26/2024

**Intersection Analysis Summary**

ID	Intersection Name	Control Type	Method	Worst Mvmt	V/C	Delay (s/veh)	LOS
2	15th Ave & 60th Street	All-way stop	HCM 2010	EB Thru	0.005	6.9	A
22	15th Ave & 40th Street	Two-way stop	HCM 2010	WB Thru	0.022	10.5	B
25	15th Ave & 50th Street	All-way stop	HCM 2010	NB Left	0.019	6.9	A
28	15th Ave & 70th Street	Two-way stop	HCM 2010	EB Thru	0.001	10.1	B





V/C, Delay, LOS: For two-way stop, these values are taken from the movement with the worst (highest) delay value. For all other control types, they are taken for the whole intersection.



Intersection Level Of Service Report  
Intersection 2: 15th Ave & 60th Street

Control Type:	All-way stop	Delay (sec / veh):	6.9
Analysis Method:	HCM 2010	Level Of Service:	A
Analysis Period:	15 minutes	Volume to Capacity (v/c):	0.005

Intersection Setup

Name	60th Street North								15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

Volumes

Name	60th Street North								15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	1	1	1	0	1	1	1	0	1	3	1	0	1	1	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	1	1	1	0	1	1	1	0	1	3	1	0	1	1	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0
Total Analysis Volume [veh/h]	0	1	1	1	0	1	1	1	0	1	3	1	0	1	1	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings				
Lanes				
Capacity per Entry Lane [veh/h]	943	943	931	943
Degree of Utilization, x	0.00	0.00	0.01	0.00
Movement, Approach, & Intersection Results				
95th-Percentile Queue Length [veh]	0.01	0.01	0.02	0.01
95th-Percentile Queue Length [m]	0.07	0.07	0.12	0.07
Approach Delay [s/veh]	6.83	6.83	6.89	6.83
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	6.85			
Intersection LOS	A			







**Intersection Level Of Service Report**  
**Intersection 22: 15th Ave & 40th Street**

Control Type: Two-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 10.5  
Level Of Service: B  
Volume to Capacity (v/c): 0.022

**Intersection Setup**

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	100.00				100.00				100.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	69	26	1	0	1	26	3	0	1	10	19	0	3	15	2
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	6.00	6.00	6.00	0.00	13.00	13.00	13.00	0.00	1.00	1.00	1.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	69	26	1	0	1	26	3	0	1	10	19	0	3	15	2
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	17	7	0	0	0	7	1	0	0	3	5	0	1	4	1
Total Analysis Volume [veh/h]	0	69	26	1	0	1	26	3	0	1	10	19	0	3	15	2
Pedestrian Volume [ped/h]	0				0				0				0			



## Intersection Settings

Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

## Movement, Approach, & Intersection Results

[illegible]







**Intersection Level Of Service Report**  
**Intersection 25: 15th Ave & 50th Street**

Control Type: All-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 6.9  
Level Of Service: A  
Volume to Capacity (v/c): 0.019

**Intersection Setup**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	10	6	1	0	1	3	1	0	1	4	9	0	1	1	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	10	6	1	0	1	3	1	0	1	4	9	0	1	1	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	3	2	0	0	0	1	0	0	0	1	2	0	0	0	0
Total Analysis Volume [veh/h]	0	10	6	1	0	1	3	1	0	1	4	9	0	1	1	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings				
Lanes				
Capacity per Entry Lane [veh/h]	896	931	1006	941
Degree of Utilization, x	0.02	0.01	0.01	0.00
Movement, Approach, & Intersection Results				
95th-Percentile Queue Length [veh]	0.06	0.02	0.04	0.01
95th-Percentile Queue Length [m]	0.44	0.12	0.32	0.07
Approach Delay [s/veh]	7.10	6.89	6.63	6.84
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	6.88			
Intersection LOS	A			







**Intersection Level Of Service Report**  
**Intersection 28: 15th Ave & 70th Street**

Control Type: Two-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 10.1  
Level Of Service: B  
Volume to Capacity (v/c): 0.001

**Intersection Setup**

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	88.51				88.51				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	1	59	1	0	1	122	1	0	1	1	2	0	1	1	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	1	59	1	0	1	122	1	0	1	1	2	0	1	1	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	0	15	0	0	0	31	0	0	0	0	1	0	0	0	0
Total Analysis Volume [veh/h]	0	1	59	1	0	1	122	1	0	1	1	2	0	1	1	1
Pedestrian Volume [ped/h]	0				0				0				0			



Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

V/C, Movement V/C Ratio	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
d_M, Delay for Movement [s/veh]	8.73	7.44	0.00	0.00	8.39	7.31	0.00	0.00	9.66	9.66	10.09	8.88	9.67	9.67	10.08	8.57
Movement LOS	A	A	A	A	A	A	A	A	A	A	B	A	A	A	B	A
95th-Percentile Queue Length [veh/in]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
95th-Percentile Queue Length [m/in]	0.02	0.02	0.02	0.02	0.01	0.01	0.01	0.01	0.11	0.11	0.11	0.11	0.08	0.08	0.08	0.08
d_A, Approach Delay [s/veh]	0.12				0.06				9.38				9.44			
Approach LOS	A				A				A				A			
d_I, Intersection Delay [s/veh]	0.42															
Intersection LOS	B															



Vistro File: K:\...\15th Ave Vistro.vistro

Report File: K:\...\Existing AM.pdf

Scenario 1 Existing AM

7/26/2024

**Network Statistics**

Number of Intersections	4
- <i>Signalized</i>	0
- <i>Roundabout</i>	0
- <i>Two-way stop</i>	2
- <i>Two-way yield</i>	0
- <i>All-way stop</i>	2
- <i>Uncontrolled</i>	0
- <i>Unknown</i>	0
Number of Links	26
Number of Zones	0
Number of Gates	0
Number of Paths	0
Number of Routes	0
Total Link Length [km]	32.0
Network Width [km]	6.3
Network Height [km]	2.8
Total Fuel Consumption [L/h]	0.0
Total Emitted CO [g/h]	0.0
Total Emitted NOx [g/h]	0.0
Total Emitted VOC [g/h]	0.0



Vistro File: K:\...\15th Ave Vistro.vistro

Report File: K:\...\Existing PM.pdf

Scenario 2 Existing PM

7/26/2024

**Intersection Analysis Summary**

ID	Intersection Name	Control Type	Method	Worst Mvmt	V/C	Delay (s/veh)	LOS
2	15th Ave & 60th Street	All-way stop	HCM 2010	EB Left	0.005	6.8	A
22	15th Ave & 40th Street	Two-way stop	HCM 2010	WB Left	0.003	10.4	B
25	15th Ave & 50th Street	All-way stop	HCM 2010	NB Left	0.031	6.9	A
28	15th Ave & 70th Street	Two-way stop	HCM 2010	EB Thru	0.002	10.6	B

V/C, Delay, LOS: For two-way stop, these values are taken from the movement with the worst (highest) delay value. For all other control types, they are taken for the whole intersection.

---







**Intersection Level Of Service Report**  
**Intersection 2: 15th Ave & 60th Street**

Control Type: All-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 6.8  
Level Of Service: A  
Volume to Capacity (v/c): 0.005

**Intersection Setup**

Name	60th Street North								15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	60th Street North								15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	1	1	1	0	1	1	2	0	2	2	1	0	1	2	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	1	1	1	0	1	1	2	0	2	2	1	0	1	2	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	0	0	0	0	0	0	1	0	1	1	0	0	0	1	0
Total Analysis Volume [veh/h]	0	1	1	1	0	1	1	2	0	2	2	1	0	1	2	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings

Lanes				
Capacity per Entry Lane [veh/h]	942	972	921	935
Degree of Utilization, x	0.00	0.00	0.01	0.00

Movement, Approach, & Intersection Results

95th-Percentile Queue Length [veh]	0.01	0.01	0.02	0.01
95th-Percentile Queue Length [m]	0.07	0.09	0.12	0.10
Approach Delay [s/veh]	6.84	6.72	6.93	6.87
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	6.85			
Intersection LOS	A			







**Intersection Level Of Service Report**  
**Intersection 22: 15th Ave & 40th Street**

Control Type: Two-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 10.4  
Level Of Service: B  
Volume to Capacity (v/c): 0.003

**Intersection Setup**

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	100.00				100.00				100.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	28	39	1	0	2	45	2	0	3	30	72	0	2	13	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	6.00	6.00	6.00	0.00	13.00	13.00	13.00	0.00	1.00	1.00	1.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	28	39	1	0	2	45	2	0	3	30	72	0	2	13	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	7	10	0	0	1	11	1	0	1	8	18	0	1	3	0
Total Analysis Volume [veh/h]	0	28	39	1	0	2	45	2	0	3	30	72	0	2	13	1
Pedestrian Volume [ped/h]	0				0				0				0			



## Intersection Settings

Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

## Movement, Approach, & Intersection Results

[illegible]







**Intersection Level Of Service Report**  
**Intersection 25: 15th Ave & 50th Street**

Control Type: All-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 6.9  
Level Of Service: A  
Volume to Capacity (v/c): 0.031

**Intersection Setup**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	13	5	1	0	1	9	1	0	1	1	30	0	4	3	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	13	5	1	0	1	9	1	0	1	1	30	0	4	3	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	3	1	0	0	0	2	0	0	0	0	8	0	1	1	0
Total Analysis Volume [veh/h]	0	13	5	1	0	1	9	1	0	1	1	30	0	4	3	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings

Lanes				
Capacity per Entry Lane [veh/h]	873	902	1043	889
Degree of Utilization, x	0.02	0.01	0.03	0.01

Movement, Approach, & Intersection Results

95th-Percentile Queue Length [veh]	0.07	0.04	0.09	0.03
95th-Percentile Queue Length [m]	0.51	0.28	0.72	0.21
Approach Delay [s/veh]	7.22	7.04	6.56	7.09
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	6.87			
Intersection LOS	A			







**Intersection Level Of Service Report**  
**Intersection 28: 15th Ave & 70th Street**

Control Type: Two-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 10.6  
Level Of Service: B  
Volume to Capacity (v/c): 0.002

**Intersection Setup**

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	88.51				88.51				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	6	87	1	0	1	120	1	0	1	1	2	0	1	1	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	10.00	10.00	10.00	0.00	15.00	15.00	15.00	0.00	16.00	16.00	16.00	0.00	8.00	8.00	8.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	6	87	1	0	1	120	1	0	1	1	2	0	1	1	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	2	22	0	0	0	30	0	0	0	0	1	0	0	0	0
Total Analysis Volume [veh/h]	0	6	87	1	0	1	120	1	0	1	1	2	0	1	1	1
Pedestrian Volume [ped/h]	0				0				0				0			



Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

[illegible]



Vistro File: K:\...\15th Ave Vistro.vistro

Report File: K:\...\Existing PM.pdf

Scenario 2 Existing PM

7/26/2024

**Network Statistics**

Number of Intersections	4
- <i>Signalized</i>	0
- <i>Roundabout</i>	0
- <i>Two-way stop</i>	2
- <i>Two-way yield</i>	0
- <i>All-way stop</i>	2
- <i>Uncontrolled</i>	0
- <i>Unknown</i>	0
Number of Links	26
Number of Zones	0
Number of Gates	0
Number of Paths	0
Number of Routes	0
Total Link Length [km]	32.0
Network Width [km]	6.3
Network Height [km]	2.8
Total Fuel Consumption [L/h]	0.0
Total Emitted CO [g/h]	0.0
Total Emitted NOx [g/h]	0.0
Total Emitted VOC [g/h]	0.0



Vistro File: K:\...\15th Ave Vistro.vistro

Report File: K:\...\Build 2045 AM.pdf

Scenario 3 Forecast AM

7/26/2024

**Intersection Analysis Summary**

ID	Intersection Name	Control Type	Method	Worst Mvmt	V/C	Delay (s/veh)	LOS
2	15th Ave & 60th Street	All-way stop	HCM 2010	NB Left	0.101	7.6	A
22	15th Ave & 40th Street	Two-way stop	HCM 2010	EB Left	0.002	14.1	B
25	15th Ave & 50th Street	All-way stop	HCM 2010	WB Thru	0.154	7.6	A
28	15th Ave & 70th Street	Two-way stop	HCM 2010	EB Thru	0.002	11.6	B

V/C, Delay, LOS: For two-way stop, these values are taken from the movement with the worst (highest) delay value. For all other control types, they are taken for the whole intersection.







**Intersection Level Of Service Report**  
**Intersection 2: 15th Ave & 60th Street**

Control Type: All-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 7.6  
Level Of Service: A  
Volume to Capacity (v/c): 0.101

**Intersection Setup**

Name	60th Street North								15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	60th Street North								15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	78	1	4	0	1	1	1	0	1	41	22	0	5	57	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	78	1	4	0	1	1	1	0	1	41	22	0	5	57	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	20	0	1	0	0	0	0	0	0	10	6	0	1	14	0
Total Analysis Volume [veh/h]	0	78	1	4	0	1	1	1	0	1	41	22	0	5	57	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings				
Lanes				
Capacity per Entry Lane [veh/h]	825	865	902	857
Degree of Utilization, x	0.10	0.00	0.07	0.07
Movement, Approach, & Intersection Results				
95th-Percentile Queue Length [veh]	0.33	0.01	0.23	0.24
95th-Percentile Queue Length [m]	2.55	0.08	1.74	1.81
Approach Delay [s/veh]	7.86	7.18	7.30	7.53
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	7.58			
Intersection LOS	A			







**Intersection Level Of Service Report**  
**Intersection 22: 15th Ave & 40th Street**

Control Type: Two-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 14.1  
Level Of Service: B  
Volume to Capacity (v/c): 0.002

**Intersection Setup**

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	100.00				100.00				100.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	85	63	1	0	18	36	27	0	1	48	23	0	8	109	51
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	6.00	6.00	6.00	0.00	13.00	13.00	13.00	0.00	1.00	1.00	1.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	85	63	1	0	18	36	27	0	1	48	23	0	8	109	51
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	21	16	0	0	5	9	7	0	0	12	6	0	2	27	13
Total Analysis Volume [veh/h]	0	85	63	1	0	18	36	27	0	1	48	23	0	8	109	51
Pedestrian Volume [ped/h]	0				0				0				0			



## Intersection Settings

Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

## Movement, Approach, & Intersection Results

[illegible]







**Intersection Level Of Service Report**  
**Intersection 25: 15th Ave & 50th Street**

Control Type: All-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 7.6  
Level Of Service: A  
Volume to Capacity (v/c): 0.154

**Intersection Setup**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	22	7	1	0	1	4	1	0	1	62	11	0	1	135	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	22	7	1	0	1	4	1	0	1	62	11	0	1	135	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	6	2	0	0	0	1	0	0	0	16	3	0	0	34	0
Total Analysis Volume [veh/h]	0	22	7	1	0	1	4	1	0	1	62	11	0	1	135	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings

Lanes				
Capacity per Entry Lane [veh/h]	803	835	894	889
Degree of Utilization, x	0.04	0.01	0.08	0.15

Movement, Approach, & Intersection Results

95th-Percentile Queue Length [veh]	0.12	0.02	0.27	0.54
95th-Percentile Queue Length [m]	0.89	0.17	2.06	4.14
Approach Delay [s/veh]	7.65	7.34	7.39	7.79
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	7.64			
Intersection LOS	A			







**Intersection Level Of Service Report**  
**Intersection 28: 15th Ave & 70th Street**

Control Type: Two-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 11.6  
Level Of Service: B  
Volume to Capacity (v/c): 0.002

**Intersection Setup**

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	88.51				88.51				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	48	73	1	0	1	150	13	0	10	1	33	0	1	1	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	48	73	1	0	1	150	13	0	10	1	33	0	1	1	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	12	18	0	0	0	38	3	0	3	0	8	0	0	0	0
Total Analysis Volume [veh/h]	0	48	73	1	0	1	150	13	0	10	1	33	0	1	1	1
Pedestrian Volume [ped/h]	0				0				0				0			



Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

[illegible]



Vistro File: K:\...\15th Ave Vistro.vistro

Report File: K:\...\Build 2045 AM.pdf

Scenario 3 Forecast AM

7/26/2024

**Network Statistics**

Number of Intersections	4
- <i>Signalized</i>	0
- <i>Roundabout</i>	0
- <i>Two-way stop</i>	2
- <i>Two-way yield</i>	0
- <i>All-way stop</i>	2
- <i>Uncontrolled</i>	0
- <i>Unknown</i>	0
Number of Links	26
Number of Zones	0
Number of Gates	0
Number of Paths	0
Number of Routes	0
Total Link Length [km]	32.0
Network Width [km]	6.3
Network Height [km]	2.8
Total Fuel Consumption [L/h]	0.0
Total Emitted CO [g/h]	0.0
Total Emitted NOx [g/h]	0.0
Total Emitted VOC [g/h]	0.0



Vistro File: K:\...\15th Ave Vistro.vistro

Scenario 4 Forecast PM

Report File: K:\...\Build 2045 PM.pdf

7/26/2024

**Intersection Analysis Summary**

ID	Intersection Name	Control Type	Method	Worst Mvmt	V/C	Delay (s/veh)	LOS
2	15th Ave & 60th Street	All-way stop	HCM 2010	NB Left	0.185	7.7	A
22	15th Ave & 40th Street	Two-way stop	HCM 2010	WB Left	0.014	16.6	C
25	15th Ave & 50th Street	All-way stop	HCM 2010	EB Thru	0.231	8.1	A
28	15th Ave & 70th Street	Two-way stop	HCM 2010	EB Thru	0.002	12.6	B

V/C, Delay, LOS: For two-way stop, these values are taken from the movement with the worst (highest) delay value. For all other control types, they are taken for the whole intersection.







**Intersection Level Of Service Report**  
**Intersection 2: 15th Ave & 60th Street**

Control Type: All-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 7.7  
Level Of Service: A  
Volume to Capacity (v/c): 0.185

**Intersection Setup**

Name	60th Street North								15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	60th Street North								15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	45	1	5	0	1	1	2	0	2	92	79	0	6	46	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	45	1	5	0	1	1	2	0	2	92	79	0	6	46	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	11	0	1	0	0	0	1	0	1	23	20	0	2	12	0
Total Analysis Volume [veh/h]	0	45	1	5	0	1	1	2	0	2	92	79	0	6	46	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings

Lanes				
Capacity per Entry Lane [veh/h]	796	855	936	851
Degree of Utilization, x	0.06	0.00	0.18	0.06

Movement, Approach, & Intersection Results

95th-Percentile Queue Length [veh]	0.20	0.01	0.68	0.20
95th-Percentile Queue Length [m]	1.56	0.11	5.14	1.52
Approach Delay [s/veh]	7.83	7.23	7.71	7.51
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	7.69			
Intersection LOS	A			







**Intersection Level Of Service Report**  
**Intersection 22: 15th Ave & 40th Street**

Control Type: Two-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 16.6  
Level Of Service: C  
Volume to Capacity (v/c): 0.014

**Intersection Setup**

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	100.00				100.00				100.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	35	57	6	0	64	71	27	0	4	138	89	0	5	80	25
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	6.00	6.00	6.00	0.00	13.00	13.00	13.00	0.00	1.00	1.00	1.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	35	57	6	0	64	71	27	0	4	138	89	0	5	80	25
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	9	14	2	0	16	18	7	0	1	35	22	0	1	20	6
Total Analysis Volume [veh/h]	0	35	57	6	0	64	71	27	0	4	138	89	0	5	80	25
Pedestrian Volume [ped/h]	0				0				0				0			



Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

[illegible]







**Intersection Level Of Service Report**  
**Intersection 25: 15th Ave & 50th Street**

Control Type: All-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 8.1  
Level Of Service: A  
Volume to Capacity (v/c): 0.231

**Intersection Setup**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	19	6	1	0	1	11	1	0	1	169	37	0	5	93	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	19	6	1	0	1	11	1	0	1	169	37	0	5	93	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	5	2	0	0	0	3	0	0	0	42	9	0	1	23	0
Total Analysis Volume [veh/h]	0	19	6	1	0	1	11	1	0	1	169	37	0	5	93	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings				
Lanes				
Capacity per Entry Lane [veh/h]	762	784	895	851
Degree of Utilization, x	0.03	0.02	0.23	0.12
Movement, Approach, & Intersection Results				
95th-Percentile Queue Length [veh]	0.11	0.05	0.89	0.39
95th-Percentile Queue Length [m]	0.81	0.39	6.81	3.00
Approach Delay [s/veh]	7.90	7.67	8.23	7.79
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	8.06			
Intersection LOS	A			







**Intersection Level Of Service Report**  
**Intersection 28: 15th Ave & 70th Street**

Control Type: Two-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 12.6  
Level Of Service: B  
Volume to Capacity (v/c): 0.002

**Intersection Setup**

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	88.51				88.51				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	45	107	1	0	8	148	4	0	18	1	79	0	1	1	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	10.00	10.00	10.00	0.00	15.00	15.00	15.00	0.00	16.00	16.00	16.00	0.00	8.00	8.00	8.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	45	107	1	0	8	148	4	0	18	1	79	0	1	1	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	11	27	0	0	2	37	1	0	5	0	20	0	0	0	0
Total Analysis Volume [veh/h]	0	45	107	1	0	8	148	4	0	18	1	79	0	1	1	1
Pedestrian Volume [ped/h]	0				0				0				0			



Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

[illegible]



Vistro File: K:\...\15th Ave Vistro.vistro

Report File: K:\...\Build 2045 PM.pdf

Scenario 4 Forecast PM

7/26/2024

**Network Statistics**

Number of Intersections	4
- <i>Signalized</i>	0
- <i>Roundabout</i>	0
- <i>Two-way stop</i>	2
- <i>Two-way yield</i>	0
- <i>All-way stop</i>	2
- <i>Uncontrolled</i>	0
- <i>Unknown</i>	0
Number of Links	26
Number of Zones	0
Number of Gates	0
Number of Paths	0
Number of Routes	0
Total Link Length [km]	32.0
Network Width [km]	6.3
Network Height [km]	2.8
Total Fuel Consumption [L/h]	0.0
Total Emitted CO [g/h]	0.0
Total Emitted NOx [g/h]	0.0
Total Emitted VOC [g/h]	0.0



Vistro File: K:\...\15th Ave Vistro.vistro

Scenario 5 Friday Summer Peak

Report File: K:\...\2045 Summer Friday Peak.pdf

7/26/2024

**Intersection Analysis Summary**

ID	Intersection Name	Control Type	Method	Worst Mvmt	V/C	Delay (s/veh)	LOS
2	15th Ave & 60th Street	All-way stop	HCM 2010	EB Thru	0.283	8.3	A
22	15th Ave & 40th Street	Two-way stop	HCM 2010	WB Left	0.018	19.3	C
25	15th Ave & 50th Street	All-way stop	HCM 2010	EB Thru	0.329	8.7	A
28	15th Ave & 70th Street	Two-way stop	HCM 2010	WB Left	0.002	14.0	B

V/C, Delay, LOS: For two-way stop, these values are taken from the movement with the worst (highest) delay value. For all other control types, they are taken for the whole intersection.







**Intersection Level Of Service Report**  
**Intersection 2: 15th Ave & 60th Street**

Control Type: All-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 8.3  
Level Of Service: A  
Volume to Capacity (v/c): 0.283

**Intersection Setup**

Name	60th Street North								15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	60th Street North								15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	45	1	5	0	1	1	2	0	2	177	79	0	6	46	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	45	1	5	0	1	1	2	0	2	177	79	0	6	46	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	11	0	1	0	0	0	1	0	1	44	20	0	2	12	0
Total Analysis Volume [veh/h]	0	45	1	5	0	1	1	2	0	2	177	79	0	6	46	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings

Lanes				
Capacity per Entry Lane [veh/h]	763	816	913	832
Degree of Utilization, x	0.07	0.00	0.28	0.06

Movement, Approach, & Intersection Results

95th-Percentile Queue Length [veh]	0.21	0.01	1.17	0.20
95th-Percentile Queue Length [m]	1.63	0.11	8.88	1.55
Approach Delay [s/veh]	8.05	7.43	8.49	7.62
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	8.29			
Intersection LOS	A			







**Intersection Level Of Service Report**  
**Intersection 22: 15th Ave & 40th Street**

Control Type: Two-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 19.3  
Level Of Service: C  
Volume to Capacity (v/c): 0.018

**Intersection Setup**

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	100.00				100.00				100.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	35	57	6	0	64	71	27	0	4	223	89	0	5	80	25
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	6.00	6.00	6.00	0.00	13.00	13.00	13.00	0.00	1.00	1.00	1.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	35	57	6	0	64	71	27	0	4	223	89	0	5	80	25
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	9	14	2	0	16	18	7	0	1	56	22	0	1	20	6
Total Analysis Volume [veh/h]	0	35	57	6	0	64	71	27	0	4	223	89	0	5	80	25
Pedestrian Volume [ped/h]	0				0				0				0			



## Intersection Settings

Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

## Movement, Approach, & Intersection Results

V/C, Movement V/C Ratio	0.00	0.02	0.00	0.00	0.00	0.04	0.00	0.00	0.00	0.01	0.41	0.09	0.00	0.02	0.15	0.02
d_M, Delay for Movement [s/veh]	9.01	7.51	0.00	0.00	8.60	7.56	0.00	0.00	18.76	18.79	17.69	14.70	19.18	19.27	13.30	10.09
Movement LOS	A	A	A	A	A	A	A	A	C	C	C	B	C	C	B	B
95th-Percentile Queue Length [veh/lane]	0.07	0.07	0.07	0.07	0.14	0.14	0.14	0.14	2.94	2.94	2.94	2.94	0.71	0.71	0.71	0.71
95th-Percentile Queue Length [m/lane]	0.56	0.56	0.56	0.56	1.04	1.04	1.04	1.04	22.38	22.38	22.38	22.38	5.42	5.42	5.42	5.42
d_A, Approach Delay [s/veh]	2.68				2.99				16.86				12.85			
Approach LOS	A				A				C				B			
d_I, Intersection Delay [s/veh]	10.92															
Intersection LOS	C															







**Intersection Level Of Service Report**  
**Intersection 25: 15th Ave & 50th Street**

Control Type: All-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 8.7  
Level Of Service: A  
Volume to Capacity (v/c): 0.329

**Intersection Setup**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	19	6	1	0	1	11	1	0	1	254	37	0	5	93	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	19	6	1	0	1	11	1	0	1	254	37	0	5	93	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	5	2	0	0	0	3	0	0	0	64	9	0	1	23	0
Total Analysis Volume [veh/h]	0	19	6	1	0	1	11	1	0	1	254	37	0	5	93	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings				
Lanes				
Capacity per Entry Lane [veh/h]	733	753	887	834
Degree of Utilization, x	0.04	0.02	0.33	0.12
Movement, Approach, & Intersection Results				
95th-Percentile Queue Length [veh]	0.11	0.05	1.45	0.40
95th-Percentile Queue Length [m]	0.84	0.40	11.01	3.07
Approach Delay [s/veh]	8.10	7.87	9.04	7.90
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	8.69			
Intersection LOS	A			







**Intersection Level Of Service Report**  
**Intersection 28: 15th Ave & 70th Street**

Control Type: Two-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 14.0  
Level Of Service: B  
Volume to Capacity (v/c): 0.002

**Intersection Setup**

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	88.51				88.51				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	45	107	1	0	8	148	4	0	18	1	164	0	1	1	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	10.00	10.00	10.00	0.00	15.00	15.00	15.00	0.00	16.00	16.00	16.00	0.00	8.00	8.00	8.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	45	107	1	0	8	148	4	0	18	1	164	0	1	1	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	11	27	0	0	2	37	1	0	5	0	41	0	0	0	0
Total Analysis Volume [veh/h]	0	45	107	1	0	8	148	4	0	18	1	164	0	1	1	1
Pedestrian Volume [ped/h]	0				0				0				0			



Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

[illegible]



Vistro File: K:\...\15th Ave Vistro.vistro

Scenario 5 Friday Summer Peak

Report File: K:\...\2045 Summer Friday Peak.pdf

7/26/2024

**Network Statistics**

Number of Intersections	4
- <i>Signalized</i>	0
- <i>Roundabout</i>	0
- <i>Two-way stop</i>	2
- <i>Two-way yield</i>	0
- <i>All-way stop</i>	2
- <i>Uncontrolled</i>	0
- <i>Unknown</i>	0
Number of Links	26
Number of Zones	0
Number of Gates	0
Number of Paths	0
Number of Routes	0
Total Link Length [km]	32.0
Network Width [km]	6.3
Network Height [km]	2.8
Total Fuel Consumption [L/h]	0.0
Total Emitted CO [g/h]	0.0
Total Emitted NOx [g/h]	0.0
Total Emitted VOC [g/h]	0.0

---



Vistro File: K:\...\15th Ave Vistro.vistro  
Report File: K:\...\High Build 2045 AM.pdf

Scenario 6 High Forecast AM Peak  
8/6/2024

### Intersection Analysis Summary

ID	Intersection Name	Control Type	Method	Worst Mvmt	V/C	Delay (s/veh)	LOS
2	15th Ave & 60th Street	All-way stop	HCM 2010	WB Thru	0.229	8.3	A
22	15th Ave & 40th Street	Two-way stop	HCM 2010	WB Left	0.135	53.8	F
25	15th Ave & 50th Street	All-way stop	HCM 2010	NB Left	0.187	8.2	A
28	15th Ave & 70th Street	Two-way stop	HCM 2010	EB Thru	0.002	13.1	B

V/C, Delay, LOS: For two-way stop, these values are taken from the movement with the worst (highest) delay value. For all other control types, they are taken for the whole intersection.







**Intersection Level Of Service Report**  
**Intersection 2: 15th Ave & 60th Street**

Control Type: All-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 8.3  
Level Of Service: A  
Volume to Capacity (v/c): 0.229

**Intersection Setup**

Name	60th Street North								15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	60th Street North								15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	83	1	10	0	1	1	1	0	1	70	22	0	20	171	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	83	1	10	0	1	1	1	0	1	70	22	0	20	171	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	21	0	3	0	0	0	0	0	0	18	6	0	5	43	0
Total Analysis Volume [veh/h]	0	83	1	10	0	1	1	1	0	1	70	22	0	20	171	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings

Lanes				
Capacity per Entry Lane [veh/h]	768	789	850	839
Degree of Utilization, x	0.12	0.00	0.11	0.23

Movement, Approach, & Intersection Results





95th-Percentile Queue Length [veh]	0.42	0.01	0.37	0.88
95th-Percentile Queue Length [m]	3.17	0.09	2.80	6.71
Approach Delay [s/veh]	8.34	7.58	7.76	8.56
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	8.30			
Intersection LOS	A			



Intersection Level Of Service Report  
Intersection 22: 15th Ave & 40th Street

Control Type:	Two-way stop	Delay (sec / veh):	53.8
Analysis Method:	HCM 2010	Level Of Service:	F
Analysis Period:	15 minutes	Volume to Capacity (v/c):	0.135

Intersection Setup

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	100.00				100.00				100.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

Volumes

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	189	79	5	0	2	38	12	0	11	110	121	0	34	278	29
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	6.00	6.00	6.00	0.00	13.00	13.00	13.00	0.00	1.00	1.00	1.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	189	79	5	0	2	38	12	0	11	110	121	0	34	278	29
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	47	20	1	0	1	10	3	0	3	28	30	0	9	70	7
Total Analysis Volume [veh/h]	0	189	79	5	0	2	38	12	0	11	110	121	0	34	278	29
Pedestrian Volume [ped/h]	0				0				0				0			



Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

[illegible]







**Intersection Level Of Service Report**  
**Intersection 25: 15th Ave & 50th Street**

Control Type: All-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 8.2  
Level Of Service: A  
Volume to Capacity (v/c): 0.187

**Intersection Setup**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	97	8	10	0	1	4	1	0	1	62	32	0	20	135	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	97	8	10	0	1	4	1	0	1	62	32	0	20	135	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	24	2	3	0	0	1	0	0	0	16	8	0	5	34	0
Total Analysis Volume [veh/h]	0	97	8	10	0	1	4	1	0	1	62	32	0	20	135	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings

Lanes				
Capacity per Entry Lane [veh/h]	785	794	865	834
Degree of Utilization, x	0.15	0.01	0.11	0.19

Movement, Approach, & Intersection Results





95th-Percentile Queue Length [veh]	0.51	0.02	0.37	0.68
95th-Percentile Queue Length [m]	3.90	0.17	2.81	5.22
Approach Delay [s/veh]	8.37	7.57	7.68	8.31
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	8.15			
Intersection LOS	A			



Intersection Level Of Service Report  
Intersection 28: 15th Ave & 70th Street

Control Type:	Two-way stop	Delay (sec / veh):	13.1
Analysis Method:	HCM 2010	Level Of Service:	B
Analysis Period:	15 minutes	Volume to Capacity (v/c):	0.002

Intersection Setup

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	88.51				88.51				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

Volumes

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	79	81	1	0	1	167	51	0	32	1	46	0	1	1	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	79	81	1	0	1	167	51	0	32	1	46	0	1	1	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	20	20	0	0	0	42	13	0	8	0	12	0	0	0	0
Total Analysis Volume [veh/h]	0	79	81	1	0	1	167	51	0	32	1	46	0	1	1	1
Pedestrian Volume [ped/h]	0				0				0				0			



Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

[illegible]



Vistro File: K:\...\15th Ave Vistro.vistro  
Report File: K:\...\High Build 2045 AM.pdf

Scenario 6 High Forecast AM Peak  
8/6/2024

### Network Statistics

Number of Intersections	4
- <i>Signalized</i>	0
- <i>Roundabout</i>	0
- <i>Two-way stop</i>	2
- <i>Two-way yield</i>	0
- <i>All-way stop</i>	2
- <i>Uncontrolled</i>	0
- <i>Unknown</i>	0
Number of Links	26
Number of Zones	0
Number of Gates	0
Number of Paths	0
Number of Routes	0
Total Link Length [km]	32.0
Network Width [km]	6.3
Network Height [km]	2.8
Total Fuel Consumption [L/h]	0.0
Total Emitted CO [g/h]	0.0
Total Emitted NOx [g/h]	0.0
Total Emitted VOC [g/h]	0.0

---



Vistro File: K:\...\15th Ave Vistro.vistro  
Report File: K:\...\High Build 2045 PM.pdf

Scenario 7 High Forecast PM Peak  
8/6/2024

### Intersection Analysis Summary

ID	Intersection Name	Control Type	Method	Worst Mvmt	V/C	Delay (s/veh)	LOS
2	15th Ave & 60th Street	All-way stop	HCM 2010	EB Thru	0.287	8.4	A
22	15th Ave & 40th Street	Two-way stop	HCM 2010	WB Thru	0.804	10,000.0	F
25	15th Ave & 50th Street	All-way stop	HCM 2010	EB Thru	0.502	10.6	B
28	15th Ave & 70th Street	Two-way stop	HCM 2010	EB Thru	0.002	15.0	B





V/C, Delay, LOS: For two-way stop, these values are taken from the movement with the worst (highest) delay value. For all other control types, they are taken for the whole intersection.



Intersection Level Of Service Report  
Intersection 2: 15th Ave & 60th Street

Control Type:	All-way stop	Delay (sec / veh):	8.4
Analysis Method:	HCM 2010	Level Of Service:	A
Analysis Period:	15 minutes	Volume to Capacity (v/c):	0.287

Intersection Setup

Name	60th Street North								15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

Volumes

Name	60th Street North								15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	45	1	5	0	1	1	3	0	3	175	79	0	6	108	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	45	1	5	0	1	1	3	0	3	175	79	0	6	108	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	11	0	1	0	0	0	1	0	1	44	20	0	2	27	0
Total Analysis Volume [veh/h]	0	45	1	5	0	1	1	3	0	3	175	79	0	6	108	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings

Lanes				
Capacity per Entry Lane [veh/h]	742	804	897	832
Degree of Utilization, x	0.07	0.01	0.29	0.14

Movement, Approach, & Intersection Results

95th-Percentile Queue Length [veh]	0.22	0.02	1.19	0.48
95th-Percentile Queue Length [m]	1.68	0.14	9.05	3.65
Approach Delay [s/veh]	8.21	7.51	8.62	8.02
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	8.40			
Intersection LOS	A			







**Intersection Level Of Service Report**  
**Intersection 22: 15th Ave & 40th Street**

Control Type: Two-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 10,000.0  
Level Of Service: F  
Volume to Capacity (v/c): 0.804

**Intersection Setup**

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	100.00				100.00				100.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	153	103	38	0	26	101	48	0	17	400	193	0	19	277	13
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	6.00	6.00	6.00	0.00	13.00	13.00	13.00	0.00	1.00	1.00	1.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	153	103	38	0	26	101	48	0	17	400	193	0	19	277	13
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	38	26	10	0	7	25	12	0	4	100	48	0	5	69	3
Total Analysis Volume [veh/h]	0	153	103	38	0	26	101	48	0	17	400	193	0	19	277	13
Pedestrian Volume [ped/h]	0				0				0				0			



Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

[illegible]







**Intersection Level Of Service Report**  
**Intersection 25: 15th Ave & 50th Street**

Control Type: All-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 10.6  
Level Of Service: B  
Volume to Capacity (v/c): 0.502

**Intersection Setup**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	58	7	1	0	1	12	1	0	1	313	111	0	5	211	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	58	7	1	0	1	12	1	0	1	313	111	0	5	211	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	15	2	0	0	0	3	0	0	0	78	28	0	1	53	0
Total Analysis Volume [veh/h]	0	58	7	1	0	1	12	1	0	1	313	111	0	5	211	1
Pedestrian Volume [ped/h]	0				0				0				0			







Intersection Settings				
Lanes				
Capacity per Entry Lane [veh/h]	649	660	846	781
Degree of Utilization, x	0.10	0.02	0.50	0.28
Movement, Approach, & Intersection Results				
95th-Percentile Queue Length [veh]	0.34	0.06	2.87	1.14
95th-Percentile Queue Length [m]	2.57	0.49	21.88	8.66
Approach Delay [s/veh]	9.17	8.57	11.47	9.38
Approach LOS	A	A	B	A
Intersection Delay [s/veh]	10.57			
Intersection LOS	B			



Intersection Level Of Service Report  
Intersection 28: 15th Ave & 70th Street

Control Type:	Two-way stop	Delay (sec / veh):	15.0
Analysis Method:	HCM 2010	Level Of Service:	B
Analysis Period:	15 minutes	Volume to Capacity (v/c):	0.002

Intersection Setup

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	88.51				88.51				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

Volumes

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	72	119	1	0	8	164	41	0	48	1	127	0	1	1	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	10.00	10.00	10.00	0.00	15.00	15.00	15.00	0.00	16.00	16.00	16.00	0.00	8.00	8.00	8.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	72	119	1	0	8	164	41	0	48	1	127	0	1	1	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	18	30	0	0	2	41	10	0	12	0	32	0	0	0	0
Total Analysis Volume [veh/h]	0	72	119	1	0	8	164	41	0	48	1	127	0	1	1	1
Pedestrian Volume [ped/h]	0				0				0				0			



Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

[illegible]



Vistro File: K:\...\15th Ave Vistro.vistro  
Report File: K:\...\High Build 2045 PM.pdf

Scenario 7 High Forecast PM Peak  
8/6/2024

### Network Statistics

Number of Intersections	4
- <i>Signalized</i>	0
- <i>Roundabout</i>	0
- <i>Two-way stop</i>	2
- <i>Two-way yield</i>	0
- <i>All-way stop</i>	2
- <i>Uncontrolled</i>	0
- <i>Unknown</i>	0
Number of Links	26
Number of Zones	0
Number of Gates	0
Number of Paths	0
Number of Routes	0
Total Link Length [km]	32.0
Network Width [km]	6.3
Network Height [km]	2.8
Total Fuel Consumption [L/h]	0.0
Total Emitted CO [g/h]	0.0
Total Emitted NOx [g/h]	0.0
Total Emitted VOC [g/h]	0.0



Vistro File: K:\...\15th Ave Vistro.vistro

Scenario 8 High Forecast Friday PM Peak

Report File: K:\...\2045 High Summer Friday Peak.pdf

8/6/2024

**Intersection Analysis Summary**

ID	Intersection Name	Control Type	Method	Worst Mvmt	V/C	Delay (s/veh)	LOS
2	15th Ave & 60th Street	All-way stop	HCM 2010	EB Thru	0.386	9.1	A
22	15th Ave & 40th Street	Two-way stop	HCM 2010	WB Thru	0.804	10,000.0	F
25	15th Ave & 50th Street	All-way stop	HCM 2010	EB Thru	0.608	12.2	B
28	15th Ave & 70th Street	Two-way stop	HCM 2010	WB Left	0.003	17.1	C

V/C, Delay, LOS: For two-way stop, these values are taken from the movement with the worst (highest) delay value. For all other control types, they are taken for the whole intersection.





---



Intersection Level Of Service Report  
Intersection 2: 15th Ave & 60th Street

Control Type:	All-way stop	Delay (sec / veh):	9.1
Analysis Method:	HCM 2010	Level Of Service:	A
Analysis Period:	15 minutes	Volume to Capacity (v/c):	0.386

Intersection Setup

Name	60th Street North								15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

Volumes

Name	60th Street North								15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	45	1	5	0	1	1	3	0	3	260	79	0	6	108	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	45	1	5	0	1	1	3	0	3	260	79	0	6	108	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	11	0	1	0	0	0	1	0	1	65	20	0	2	27	0
Total Analysis Volume [veh/h]	0	45	1	5	0	1	1	3	0	3	260	79	0	6	108	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings

Lanes				
Capacity per Entry Lane [veh/h]	714	770	885	814
Degree of Utilization, x	0.07	0.01	0.39	0.14

Movement, Approach, & Intersection Results





95th-Percentile Queue Length [veh]	0.23	0.02	1.84	0.49
95th-Percentile Queue Length [m]	1.75	0.15	14.02	3.74
Approach Delay [s/veh]	8.43	7.71	9.61	8.15
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	9.14			
Intersection LOS	A			



Intersection Level Of Service Report  
Intersection 22: 15th Ave & 40th Street

Control Type:	Two-way stop	Delay (sec / veh):	10,000.0
Analysis Method:	HCM 2010	Level Of Service:	F
Analysis Period:	15 minutes	Volume to Capacity (v/c):	0.804

Intersection Setup

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	100.00				100.00				100.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

Volumes

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	153	103	38	0	26	101	48	0	17	485	193	0	19	277	13
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	6.00	6.00	6.00	0.00	13.00	13.00	13.00	0.00	1.00	1.00	1.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	153	103	38	0	26	101	48	0	17	485	193	0	19	277	13
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	38	26	10	0	7	25	12	0	4	121	48	0	5	69	3
Total Analysis Volume [veh/h]	0	153	103	38	0	26	101	48	0	17	485	193	0	19	277	13
Pedestrian Volume [ped/h]	0				0				0				0			



Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

[illegible]







**Intersection Level Of Service Report**  
**Intersection 25: 15th Ave & 50th Street**

Control Type: All-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 12.2  
Level Of Service: B  
Volume to Capacity (v/c): 0.608

**Intersection Setup**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	58	7	1	0	1	12	1	0	1	398	111	0	5	211	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	58	7	1	0	1	12	1	0	1	398	111	0	5	211	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	15	2	0	0	0	3	0	0	0	100	28	0	1	53	0
Total Analysis Volume [veh/h]	0	58	7	1	0	1	12	1	0	1	398	111	0	5	211	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings				
Lanes				
Capacity per Entry Lane [veh/h]	627	636	838	764
Degree of Utilization, x	0.11	0.02	0.61	0.28
Movement, Approach, & Intersection Results				
95th-Percentile Queue Length [veh]	0.35	0.07	4.23	1.17
95th-Percentile Queue Length [m]	2.67	0.51	32.20	8.92
Approach Delay [s/veh]	9.41	8.78	13.73	9.57
Approach LOS	A	A	B	A
Intersection Delay [s/veh]	12.17			
Intersection LOS	B			







**Intersection Level Of Service Report**  
**Intersection 28: 15th Ave & 70th Street**

Control Type: Two-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 17.1  
Level Of Service: C  
Volume to Capacity (v/c): 0.003

**Intersection Setup**

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	88.51				88.51				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	72	119	1	0	8	164	41	0	48	1	212	0	1	1	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	10.00	10.00	10.00	0.00	15.00	15.00	15.00	0.00	16.00	16.00	16.00	0.00	8.00	8.00	8.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	72	119	1	0	8	164	41	0	48	1	212	0	1	1	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	18	30	0	0	2	41	10	0	12	0	53	0	0	0	0
Total Analysis Volume [veh/h]	0	72	119	1	0	8	164	41	0	48	1	212	0	1	1	1
Pedestrian Volume [ped/h]	0				0				0				0			



Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

[illegible]



Vistro File: K:\...\15th Ave Vistro.vistro

Scenario 8 High Forecast Friday PM Peak

Report File: K:\...\2045 High Summer Friday Peak.pdf

8/6/2024

**Network Statistics**

Number of Intersections	4
- <i>Signalized</i>	0
- <i>Roundabout</i>	0
- <i>Two-way stop</i>	2
- <i>Two-way yield</i>	0
- <i>All-way stop</i>	2
- <i>Uncontrolled</i>	0
- <i>Unknown</i>	0
Number of Links	26
Number of Zones	0
Number of Gates	0
Number of Paths	0
Number of Routes	0
Total Link Length [km]	32.0
Network Width [km]	6.3
Network Height [km]	2.8
Total Fuel Consumption [L/h]	0.0
Total Emitted CO [g/h]	0.0
Total Emitted NOx [g/h]	0.0
Total Emitted VOC [g/h]	0.0



Vistro File: K:\...\15th Ave Vistro.vistro

Scenario 6 High Forecast AM Peak

Report File: K:\...\High Build 2045 AM Mitigation Flip.pdf

8/6/2024

**Intersection Analysis Summary**

ID	Intersection Name	Control Type	Method	Worst Mvmt	V/C	Delay (s/veh)	LOS
2	15th Ave & 60th Street	All-way stop	HCM 2010	WB Thru	0.229	8.3	A
22	15th Ave & 40th Street	Two-way stop	HCM 2010	NB Left	0.510	34.5	D
25	15th Ave & 50th Street	All-way stop	HCM 2010	NB Left	0.187	8.2	A
28	15th Ave & 70th Street	Two-way stop	HCM 2010	EB Thru	0.002	13.1	B

V/C, Delay, LOS: For two-way stop, these values are taken from the movement with the worst (highest) delay value. For all other control types, they are taken for the whole intersection.







**Intersection Level Of Service Report**  
**Intersection 2: 15th Ave & 60th Street**

Control Type: All-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 8.3  
Level Of Service: A  
Volume to Capacity (v/c): 0.229

**Intersection Setup**

Name	60th Street North								15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	60th Street North								15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	83	1	10	0	1	1	1	0	1	70	22	0	20	171	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	83	1	10	0	1	1	1	0	1	70	22	0	20	171	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	21	0	3	0	0	0	0	0	0	18	6	0	5	43	0
Total Analysis Volume [veh/h]	0	83	1	10	0	1	1	1	0	1	70	22	0	20	171	1
Pedestrian Volume [ped/h]	0				0				0				0			







Intersection Settings				
Lanes				
Capacity per Entry Lane [veh/h]	768	789	850	839
Degree of Utilization, x	0.12	0.00	0.11	0.23
Movement, Approach, & Intersection Results				
95th-Percentile Queue Length [veh]	0.42	0.01	0.37	0.88
95th-Percentile Queue Length [m]	3.17	0.09	2.80	6.71
Approach Delay [s/veh]	8.34	7.58	7.76	8.56
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	8.30			
Intersection LOS	A			



Intersection Level Of Service Report  
Intersection 22: 15th Ave & 40th Street

Control Type:	Two-way stop	Delay (sec / veh):	34.5
Analysis Method:	HCM 2010	Level Of Service:	D
Analysis Period:	15 minutes	Volume to Capacity (v/c):	0.510

Intersection Setup

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	100.00				100.00				100.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

Volumes

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	189	79	5	0	2	38	12	0	11	110	121	0	34	278	29
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	6.00	6.00	6.00	0.00	13.00	13.00	13.00	0.00	1.00	1.00	1.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	189	79	5	0	2	38	12	0	11	110	121	0	34	278	29
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	47	20	1	0	1	10	3	0	3	28	30	0	9	70	7
Total Analysis Volume [veh/h]	0	189	79	5	0	2	38	12	0	11	110	121	0	34	278	29
Pedestrian Volume [ped/h]	0				0				0				0			



Priority Scheme	Stop	Stop	Free	Free
Flared Lane	No	No		
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance	No	No		
Number of Storage Spaces in Median	0	0	0	0

[illegible]







**Intersection Level Of Service Report**  
**Intersection 25: 15th Ave & 50th Street**

Control Type: All-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 8.2  
Level Of Service: A  
Volume to Capacity (v/c): 0.187

**Intersection Setup**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	97	8	10	0	1	4	1	0	1	62	32	0	20	135	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	97	8	10	0	1	4	1	0	1	62	32	0	20	135	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	24	2	3	0	0	1	0	0	0	16	8	0	5	34	0
Total Analysis Volume [veh/h]	0	97	8	10	0	1	4	1	0	1	62	32	0	20	135	1
Pedestrian Volume [ped/h]	0				0				0				0			







Intersection Settings				
Lanes				
Capacity per Entry Lane [veh/h]	785	794	865	834
Degree of Utilization, x	0.15	0.01	0.11	0.19
Movement, Approach, & Intersection Results				
95th-Percentile Queue Length [veh]	0.51	0.02	0.37	0.68
95th-Percentile Queue Length [m]	3.90	0.17	2.81	5.22
Approach Delay [s/veh]	8.37	7.57	7.68	8.31
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	8.15			
Intersection LOS	A			



Intersection Level Of Service Report  
Intersection 28: 15th Ave & 70th Street

Control Type:	Two-way stop	Delay (sec / veh):	13.1
Analysis Method:	HCM 2010	Level Of Service:	B
Analysis Period:	15 minutes	Volume to Capacity (v/c):	0.002

Intersection Setup

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	88.51				88.51				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

Volumes

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	79	81	1	0	1	167	51	0	32	1	46	0	1	1	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	79	81	1	0	1	167	51	0	32	1	46	0	1	1	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	20	20	0	0	0	42	13	0	8	0	12	0	0	0	0
Total Analysis Volume [veh/h]	0	79	81	1	0	1	167	51	0	32	1	46	0	1	1	1
Pedestrian Volume [ped/h]	0				0				0				0			



Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

[illegible]



Vistro File: K:\...\15th Ave Vistro.vistro

Scenario 6 High Forecast AM Peak

Report File: K:\...\High Build 2045 AM Mitigation Flip.pdf

8/6/2024

**Network Statistics**

Number of Intersections	4
- <i>Signalized</i>	0
- <i>Roundabout</i>	0
- <i>Two-way stop</i>	2
- <i>Two-way yield</i>	0
- <i>All-way stop</i>	2
- <i>Uncontrolled</i>	0
- <i>Unknown</i>	0
Number of Links	26
Number of Zones	0
Number of Gates	0
Number of Paths	0
Number of Routes	0
Total Link Length [km]	32.0
Network Width [km]	6.3
Network Height [km]	2.8
Total Fuel Consumption [L/h]	0.0
Total Emitted CO [g/h]	0.0
Total Emitted NOx [g/h]	0.0
Total Emitted VOC [g/h]	0.0

---



Vistro File: K:\...\15th Ave Vistro.vistro

Scenario 7 High Forecast PM Peak

Report File: K:\...\High Build 2045 PM Mitigation Flip.pdf

8/6/2024

**Intersection Analysis Summary**

ID	Intersection Name	Control Type	Method	Worst Mvmt	V/C	Delay (s/veh)	LOS
2	15th Ave & 60th Street	All-way stop	HCM 2010	EB Thru	0.287	8.4	A
22	15th Ave & 40th Street	Two-way stop	HCM 2010	NB Left	1.030	286.2	F
25	15th Ave & 50th Street	All-way stop	HCM 2010	EB Thru	0.502	10.6	B
28	15th Ave & 70th Street	Two-way stop	HCM 2010	EB Thru	0.002	15.0	B





V/C, Delay, LOS: For two-way stop, these values are taken from the movement with the worst (highest) delay value. For all other control types, they are taken for the whole intersection.



Intersection Level Of Service Report  
Intersection 2: 15th Ave & 60th Street

Control Type:	All-way stop	Delay (sec / veh):	8.4
Analysis Method:	HCM 2010	Level Of Service:	A
Analysis Period:	15 minutes	Volume to Capacity (v/c):	0.287

Intersection Setup

Name	60th Street North								15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

Volumes

Name	60th Street North								15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	45	1	5	0	1	1	3	0	3	175	79	0	6	108	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	45	1	5	0	1	1	3	0	3	175	79	0	6	108	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	11	0	1	0	0	0	1	0	1	44	20	0	2	27	0
Total Analysis Volume [veh/h]	0	45	1	5	0	1	1	3	0	3	175	79	0	6	108	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings				
Lanes				
Capacity per Entry Lane [veh/h]	742	804	897	832
Degree of Utilization, x	0.07	0.01	0.29	0.14
Movement, Approach, & Intersection Results				
95th-Percentile Queue Length [veh]	0.22	0.02	1.19	0.48
95th-Percentile Queue Length [m]	1.68	0.14	9.05	3.65
Approach Delay [s/veh]	8.21	7.51	8.62	8.02
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	8.40			
Intersection LOS	A			







**Intersection Level Of Service Report**  
**Intersection 22: 15th Ave & 40th Street**

Control Type: Two-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 286.2  
Level Of Service: F  
Volume to Capacity (v/c): 1.030

**Intersection Setup**

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	100.00				100.00				100.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	153	103	38	0	26	101	48	0	17	400	193	0	19	277	13
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	6.00	6.00	6.00	0.00	13.00	13.00	13.00	0.00	1.00	1.00	1.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	153	103	38	0	26	101	48	0	17	400	193	0	19	277	13
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	38	26	10	0	7	25	12	0	4	100	48	0	5	69	3
Total Analysis Volume [veh/h]	0	153	103	38	0	26	101	48	0	17	400	193	0	19	277	13
Pedestrian Volume [ped/h]	0				0				0				0			



Priority Scheme	Stop	Stop	Free	Free
Flared Lane	No	No		
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance	No	No		
Number of Storage Spaces in Median	0	0	0	0

[illegible]







**Intersection Level Of Service Report**  
**Intersection 25: 15th Ave & 50th Street**

Control Type: All-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 10.6  
Level Of Service: B  
Volume to Capacity (v/c): 0.502

**Intersection Setup**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	58	7	1	0	1	12	1	0	1	313	111	0	5	211	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	58	7	1	0	1	12	1	0	1	313	111	0	5	211	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	15	2	0	0	0	3	0	0	0	78	28	0	1	53	0
Total Analysis Volume [veh/h]	0	58	7	1	0	1	12	1	0	1	313	111	0	5	211	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings

Lanes				
Capacity per Entry Lane [veh/h]	649	660	846	781
Degree of Utilization, x	0.10	0.02	0.50	0.28

Movement, Approach, & Intersection Results





95th-Percentile Queue Length [veh]	0.34	0.06	2.87	1.14
95th-Percentile Queue Length [m]	2.57	0.49	21.88	8.66
Approach Delay [s/veh]	9.17	8.57	11.47	9.38
Approach LOS	A	A	B	A
Intersection Delay [s/veh]	10.57			
Intersection LOS	B			



Intersection Level Of Service Report  
Intersection 28: 15th Ave & 70th Street

Control Type:	Two-way stop	Delay (sec / veh):	15.0
Analysis Method:	HCM 2010	Level Of Service:	B
Analysis Period:	15 minutes	Volume to Capacity (v/c):	0.002

Intersection Setup

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	88.51				88.51				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

Volumes

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	72	119	1	0	8	164	41	0	48	1	127	0	1	1	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	10.00	10.00	10.00	0.00	15.00	15.00	15.00	0.00	16.00	16.00	16.00	0.00	8.00	8.00	8.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	72	119	1	0	8	164	41	0	48	1	127	0	1	1	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	18	30	0	0	2	41	10	0	12	0	32	0	0	0	0
Total Analysis Volume [veh/h]	0	72	119	1	0	8	164	41	0	48	1	127	0	1	1	1
Pedestrian Volume [ped/h]	0				0				0				0			



Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

[illegible]



Vistro File: K:\...\15th Ave Vistro.vistro

Scenario 7 High Forecast PM Peak

Report File: K:\...\High Build 2045 PM Mitigation Flip.pdf

8/6/2024

**Network Statistics**

Number of Intersections	4
- <i>Signalized</i>	0
- <i>Roundabout</i>	0
- <i>Two-way stop</i>	2
- <i>Two-way yield</i>	0
- <i>All-way stop</i>	2
- <i>Uncontrolled</i>	0
- <i>Unknown</i>	0
Number of Links	26
Number of Zones	0
Number of Gates	0
Number of Paths	0
Number of Routes	0
Total Link Length [km]	32.0
Network Width [km]	6.3
Network Height [km]	2.8
Total Fuel Consumption [L/h]	0.0
Total Emitted CO [g/h]	0.0
Total Emitted NOx [g/h]	0.0
Total Emitted VOC [g/h]	0.0



Vistro File: K:\...\15th Ave Vistro.vistro

Scenario 8 High Forecast Friday PM Peak

Report File: K:\...\High Build 2045 PM Mitigation RAB.pdf

8/6/2024

**Intersection Analysis Summary**

ID	Intersection Name	Control Type	Method	Worst Mvmt	V/C	Delay (s/veh)	LOS
2	15th Ave & 60th Street	All-way stop	HCM 2010	EB Thru	0.386	9.1	A
22	15th Ave & 40th Street	Roundabout	HCM 2010	EB Thru		13.6	B
25	15th Ave & 50th Street	All-way stop	HCM 2010	EB Thru	0.608	12.2	B
28	15th Ave & 70th Street	Two-way stop	HCM 2010	WB Left	0.003	17.1	C





V/C, Delay, LOS: For two-way stop, these values are taken from the movement with the worst (highest) delay value. For all other control types, they are taken for the whole intersection.



Intersection Level Of Service Report  
Intersection 2: 15th Ave & 60th Street

Control Type:	All-way stop	Delay (sec / veh):	9.1
Analysis Method:	HCM 2010	Level Of Service:	A
Analysis Period:	15 minutes	Volume to Capacity (v/c):	0.386

Intersection Setup

Name	60th Street North								15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

Volumes





Name	60th Street North								15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	45	1	5	0	1	1	3	0	3	260	79	0	6	108	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	45	1	5	0	1	1	3	0	3	260	79	0	6	108	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	11	0	1	0	0	0	1	0	1	65	20	0	2	27	0
Total Analysis Volume [veh/h]	0	45	1	5	0	1	1	3	0	3	260	79	0	6	108	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings				
Lanes				
Capacity per Entry Lane [veh/h]	714	770	885	814
Degree of Utilization, x	0.07	0.01	0.39	0.14
Movement, Approach, & Intersection Results				
95th-Percentile Queue Length [veh]	0.23	0.02	1.84	0.49
95th-Percentile Queue Length [m]	1.75	0.15	14.02	3.74
Approach Delay [s/veh]	8.43	7.71	9.61	8.15
Approach LOS	A	A	A	A
Intersection Delay [s/veh]	9.14			
Intersection LOS	A			



**Intersection Level Of Service Report**  
**Intersection 22: 15th Ave & 40th Street**Control Type:  
Analysis Method:  
Analysis Period:Roundabout  
HCM 2010  
15 minutesDelay (sec / veh):  
Level Of Service:13.6  
B**Intersection Setup**

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	100.00				100.00				100.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	40th Street North				40th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	153	103	38	0	26	101	48	0	17	485	193	0	19	277	13
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	6.00	6.00	6.00	0.00	13.00	13.00	13.00	0.00	1.00	1.00	1.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	153	103	38	0	26	101	48	0	17	485	193	0	19	277	13
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	38	26	10	0	7	25	12	0	4	121	48	0	5	69	3
Total Analysis Volume [veh/h]	0	153	103	38	0	26	101	48	0	17	485	193	0	19	277	13
Pedestrian Volume [ped/h]	0				0				0				0			



Number of Conflicting Circulating Lanes	1				1				1				1			
Circulating Flow Rate [veh/h]	536				464				163				289			
Exiting Flow Rate [veh/h]	328				140				499				560			
Demand Flow Rate [veh/h]	0	153	103	38	0	26	101	48	0	17	485	193	0	19	277	13
Adjusted Demand Flow Rate [veh/h]	0	153	103	38	0	26	101	48	0	17	485	193	0	19	277	13

Overwrite Calculated Critical Headway	No	No	No	No
User-Defined Critical Headway [s]	4.00	4.00	4.00	4.00
Overwrite Calculated Follow-Up Time	No	No	No	No
User-Defined Follow-Up Time [s]	3.00	3.00	3.00	3.00
A (intercept)	1130.00	1130.00	1130.00	1130.00
B (coefficient)	0.00100	0.00100	0.00100	0.00100
HV Adjustment Factor	0.94	0.88	0.99	0.98
Entry Flow Rate [veh/h]	312	198	702	316
Capacity of Entry and Bypass Lanes [veh/h]	661	711	961	847
Pedestrian Impedance	1.00	1.00	1.00	1.00
Capacity per Entry Lane [veh/h]	624	629	951	831
X, volume / capacity	0.47	0.28	0.73	0.37

Lane LOS	B	A	C	A
95th-Percentile Queue Length [veh]	2.52	1.13	6.74	1.73
95th-Percentile Queue Length [m]	19.22	8.64	51.33	13.20
Approach Delay [s/veh]	13.18	9.31	16.99	8.75
Approach LOS	B	A	C	A
Intersection Delay [s/veh]	13.59			
Intersection LOS	B			







**Intersection Level Of Service Report**  
**Intersection 25: 15th Ave & 50th Street**

Control Type: All-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 12.2  
Level Of Service: B  
Volume to Capacity (v/c): 0.608

**Intersection Setup**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	50.00				50.00				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	50th Street North				50th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	58	7	1	0	1	12	1	0	1	398	111	0	5	211	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00	0.00	2.00	2.00	2.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	58	7	1	0	1	12	1	0	1	398	111	0	5	211	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	15	2	0	0	0	3	0	0	0	100	28	0	1	53	0
Total Analysis Volume [veh/h]	0	58	7	1	0	1	12	1	0	1	398	111	0	5	211	1
Pedestrian Volume [ped/h]	0				0				0				0			



Intersection Settings				
Lanes				
Capacity per Entry Lane [veh/h]	627	636	838	764
Degree of Utilization, x	0.11	0.02	0.61	0.28
Movement, Approach, & Intersection Results				
95th-Percentile Queue Length [veh]	0.35	0.07	4.23	1.17
95th-Percentile Queue Length [m]	2.67	0.51	32.20	8.92
Approach Delay [s/veh]	9.41	8.78	13.73	9.57
Approach LOS	A	A	B	A
Intersection Delay [s/veh]	12.17			
Intersection LOS	B			







**Intersection Level Of Service Report**  
**Intersection 28: 15th Ave & 70th Street**

Control Type: Two-way stop  
Analysis Method: HCM 2010  
Analysis Period: 15 minutes

Delay (sec / veh): 17.1  
Level Of Service: C  
Volume to Capacity (v/c): 0.003

**Intersection Setup**

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Approach	Northbound				Southbound				Eastbound				Westbound			
Lane Configuration																
Turning Movement	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right	U-tu	Left	Thru	Right
Lane Width [m]	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
No. of Lanes in Entry Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Entry Pocket Length [m]	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48	30.48
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [m]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [km/h]	88.51				88.51				50.00				50.00			
Grade [%]	0.00				0.00				0.00				0.00			
Crosswalk	Yes				Yes				Yes				Yes			

**Volumes**

Name	70th Street North				70th Street North				15th Avenue North				15th Avenue North			
Base Volume Input [veh/h]	0	72	119	1	0	8	164	41	0	48	1	212	0	1	1	1
Base Volume Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Heavy Vehicles Percentage [%]	0.00	10.00	10.00	10.00	0.00	15.00	15.00	15.00	0.00	16.00	16.00	16.00	0.00	8.00	8.00	8.00
Growth Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	0	72	119	1	0	8	164	41	0	48	1	212	0	1	1	1
Peak Hour Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Other Adjustment Factor	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Total 15-Minute Volume [veh/h]	0	18	30	0	0	2	41	10	0	12	0	53	0	0	0	0
Total Analysis Volume [veh/h]	0	72	119	1	0	8	164	41	0	48	1	212	0	1	1	1
Pedestrian Volume [ped/h]	0				0				0				0			



Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	No
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	No
Number of Storage Spaces in Median	0	0	0	0

[illegible]



Vistro File: K:\...\15th Ave Vistro.vistro

Scenario 8 High Forecast Friday PM Peak

Report File: K:\...\High Build 2045 PM Mitigation RAB.pdf

8/6/2024

**Network Statistics**

Number of Intersections	4
- <i>Signalized</i>	0
- <i>Roundabout</i>	1
- <i>Two-way stop</i>	1
- <i>Two-way yield</i>	0
- <i>All-way stop</i>	2
- <i>Uncontrolled</i>	0
- <i>Unknown</i>	0
Number of Links	26
Number of Zones	0
Number of Gates	0
Number of Paths	0
Number of Routes	0
Total Link Length [km]	32.0
Network Width [km]	6.3
Network Height [km]	2.8
Total Fuel Consumption [L/h]	0.0
Total Emitted CO [g/h]	0.0
Total Emitted NOx [g/h]	0.0
Total Emitted VOC [g/h]	0.0

---



# Appendix C

## FEMA Floodplain Maps



NOTES TO USERS

This map is for use in administering the National Flood Insurance Program. It does not necessarily identify all areas subject to flooding, particularly from local drainage sources of small size. The community map repository should be consulted for possible updated or additional flood hazard information.

To obtain more detailed information in areas where **Base Flood Elevations (BFEs)** and/or **floodways** have been determined, users are encouraged to consult the Flood Profiles and Floodway Data and/or Summary of Stillwater Elevations tables contained within the Flood Insurance Study (FIS) report that accompanies this FIRM. Users should be aware that BFEs shown on the FIRM represent rounded whole-foot elevations. These BFEs are intended for flood insurance rating purposes only and should not be used as the sole source of flood elevation information. Accordingly, flood elevation data presented in the FIS report should be utilized in conjunction with the FIRM for purposes of construction and/or floodplain management.

**Coastal Base Flood Elevations** shown on this map apply only landward of 0' 0" North American Vertical Datum of 1988 (NAVD 88). Users of this FIRM should be aware that coastal flood elevations are also provided in the Summary of Stillwater Elevations tables in the Flood Insurance Study Report for this jurisdiction. Elevations shown in the Summary of Stillwater Elevations table should be used for construction and/or floodplain management purposes when they are higher than the elevations shown on this FIRM.

Boundaries of the **floodways** were computed at cross sections and interpolated between cross sections. The floodways were based on hydraulic considerations with regard to requirements of the National Flood Insurance Program. Floodway widths and other pertinent floodway data are provided in the Flood Insurance Study report for this jurisdiction.

Certain areas not in Special Flood Hazard Areas may be protected by **flood control structures**. Refer to Section 2.4 "Flood Protection Measures" of the Flood Insurance Study report for information on flood control structures in this jurisdiction.

The **projection** used in the preparation of this map was Universal Transverse Mercator (UTM) zone 14. The **horizontal datum** was NAD 83, GRS 80 spheroid. Differences in datum, spheroid, projection or State Plane zones used in the production of FIRMs for adjacent jurisdictions may result in slight positional differences in map features across jurisdiction boundaries. These differences do not affect the accuracy of this FIRM.

Flood elevations on this map are referenced to the North American Vertical Datum of 1988. These flood elevations must be compared to structure and ground elevations referenced to the same vertical datum. For information regarding conversion between the National Geodetic Vertical Datum of 1929 and the North American Vertical Datum of 1988, visit the National Geodetic Survey website at <http://www.ngs.noaa.gov> or contact the National Geodetic Survey at the following address:

NGS Information Services  
NOAA, NGS12  
National Geodetic Survey  
SSMC-3, #9202  
1315 East-West Highway  
Silver Spring, Maryland 20910-3282  
(301) 713-3242

To obtain current elevation, description, and/or location information about the **bench marks** shown on this map, please contact the Information Services Branch of the National Geodetic Survey at (301) 713-3242, or visit their website at <http://www.ngs.noaa.gov>.

**Base map** information shown on this FIRM was derived from aerial photography produced for Clay County dated 2005 at a scale of 1:12,000 and aerial photography produced for USDA dated 2004 at a scale of 1:12,000.

The **profile baselines** depicted on this map represent the hydraulic modeling baselines that match the flood profiles in the FIS report. As a result of improved topographic data, the profile baseline, in some cases, may deviate significantly from the channel centerline or appear outside the Special Flood Hazard Area.

**Corporate limits** shown on this map are based on the best data available at the time of publication. Because changes due to annexations or de-annexations may have occurred after this map was published, map users should contact appropriate community officials to verify current corporate limit locations.


Please refer to the separately printed **Map Index** for an overview map of the county showing the layout of map panels, community map repository addresses, and a Listing of Communities table containing National Flood Insurance Program dates for each community as well as a listing of the panels on which each community is located.

For information on available products associated with this FIRM visit the **Map Service Center (MSC)** website at <http://msc.fema.gov>. Available products may include previously issued Letters of Map Change, a Flood Insurance Study Report, and/or digital versions of this map. Many of these products can be ordered or obtained directly from the MSC website.

If you have **questions about this map**, how to order products, or the National Flood Insurance Program in general, please call the **FEMA Map Information eXchange (FMIX)** at 1-877-FEMA-MAP (1-877-336-2627) or visit the FEMA website at <http://www.fema.gov/business/info>.

ADMINISTRATIVE FLOODWAY

ADMINISTRATIVE FLOODWAY\*  
(SUBJECT TO LOCAL REGULATIONS)




LEGEND

- SPECIAL FLOOD HAZARD AREAS (SFHAs) SUBJECT TO INUNDATION BY THE 1% ANNUAL CHANCE FLOOD**
- The 1% annual chance flood (100-year flood), also known as the base flood, is the flood that has a 1% chance of being equaled or exceeded in any given year. The Special Flood Hazard Area is the area subject to flooding by the 1% annual chance flood. Areas of Special Flood Hazard include Zones A, AE, AH, AO, AR, A99, V, and VE. The Base Flood Elevation is the water-surface elevation of the 1% annual chance flood.
- ZONE A** No Base Flood Elevations determined.
- ZONE AE** Base Flood Elevations determined.
- ZONE AH** Flood depths of 1 to 3 feet (usually areas of ponding); Base Flood Elevations determined.
- ZONE AO** Flood depths of 1 to 3 feet (usually sheet flow on sloping terrain); average depths determined. For areas of alluvial fan flooding, velocities also determined.
- ZONE AR** Special Flood Hazard Areas formerly protected from the 1% annual chance flood by a flood control system that was subsequently decertified. Zone AR indicates that the former flood control system is being restored to provide protection from the 1% annual chance or greater flood.
- ZONE A99** Area to be protected from 1% annual chance flood by a Federal flood protection system under construction; no Base Flood Elevations determined.
- ZONE V** Coastal flood zone with velocity hazard (wave action); no Base Flood Elevations determined.
- ZONE VE** Coastal flood zone with velocity hazard (wave action); Base Flood Elevations determined.
- FLOODWAY AREAS IN ZONE AE**
- The floodway is the channel of a stream plus any adjacent floodplain areas that must be kept free of encroachment so that the 1% annual chance flood can be carried without substantial increases in flood heights.
- OTHER FLOOD AREAS**
- ZONE X** Areas of 0.2% annual chance flood; areas of 1% annual chance flood with average depths of less than 1 foot or with drainage areas less than 1 square mile; and areas protected by levees from 1% annual chance flood.
- OTHER AREAS**
- ZONE X** Areas determined to be outside the 0.2% annual chance floodplain.
- ZONE D** Areas in which flood hazards are undetermined, but possible.
- COASTAL BARRIER RESOURCES SYSTEM (CBRS) AREAS**
- OTHERWISE PROTECTED AREAS (OPAs)**
- CBRS areas and OPAs are normally located within or adjacent to Special Flood Hazard Areas.
- 1% annual chance floodplain boundary  
0.2% annual chance floodplain boundary  
Floodway boundary  
Zone D boundary  
CBRS and OPA boundary  
Boundary dividing Special Flood Hazard Areas of different Base Flood Elevations, flood depths or flood velocities.  
Base Flood Elevation line and value; elevation in feet\*  
Base Flood Elevation value where uniform within zone; elevation in feet\*  
\*Referenced to the North American Vertical Datum of 1988
- Cross section line**  
Transect line  
Geographic coordinates referenced to the North American Datum of 1983 (NAD 83) Western Hemisphere  
1000-meter Universal Transverse Mercator grid values, zone 14  
Bench mark (see explanation in Notes to Users section of this FIRM panel)  
River Mile

MAP REPOSITORY  
Refer to listing of Map Repositories on Map Index  
EFFECTIVE DATE OF COUNTYWIDE  
APRIL 17, 2012  
EFFECTIVE DATE(S) OF REVISION(S) TO THIS PANEL

For community map revision history prior to countywide mapping, refer to the Community Map History table located in the Flood Insurance Study report for this jurisdiction.

To determine if flood insurance is available in this community contact your insurance agent or call the National Flood Insurance Program at 1-800-638-6620.



**NATIONAL FLOOD INSURANCE PROGRAM**

**PANEL 0339E**

**FIRM**

**FLOOD INSURANCE RATE MAP**

**CLAY COUNTY, MINNESOTA AND INCORPORATED AREAS**

**PANEL 339 OF 750**

(SEE MAP INDEX FOR FIRM PANEL LAYOUT)

**CONTAINS:**

COMMUNITY	NUMBER	PANEL	SUFFIX
CLAY COUNTY	275235	0339	E
DILWORTH, CITY OF	270080	0339	E

Notice to User: The **Map Number** shown below should be used when placing map orders; the **Community Number** shown above should be used on insurance applications for the subject community.

**MAP NUMBER**  
**27027C0339E**  
**EFFECTIVE DATE**  
**APRIL 17, 2012**

**Federal Emergency Management Agency**







# Appendix D

## SRC Meeting Minutes





# 15<sup>th</sup> Ave N Corridor Study – SRC Meeting #1

## Meeting Minutes

**Date:** 7/22/2024

**Time:** 11:00 AM

**Facilitator:** Scott Middaugh

**Attendees:** Jeff Winter – Moland Township; Peyton Mastera – City of Dilworth; Michael Maddox – Metro COG; Justin Sorum – Clay County; Scott Middaugh, Veronica Richfield, Todd Hummel – KLJ

### Introductions

1. Introductions for the group were made. Representatives from Moorhead and Oakport Townships were not present.
2. Carol Kurtyka (Moorhead Township) was out of town this week so was not able to attend.
3. Tim Brendemuhl (Oakport Township) was invited to the meeting but did not respond. Scott M will follow up with him later to ensure he is the correct person to contact for future SRC Meetings.

### Study Overview

1. Scott M gave an overview of the study.
  - a. 3 miles of 15<sup>th</sup> Ave N between CSAH 9 and CSAH 11
  - b. 15<sup>th</sup> Ave N was identified in the TH 10 corridor study as an east/west reliever route for the metro area.
  - c. Study aims to look at future improvements to the roadway along with future ownership and maintenance of the roadway.
  - d. Study will be completed by December 2024.
2. SRC members will help guide the study and review materials before going to the public.
  - a. SRC comprised of Metro COG, Clay County, City of Dilworth, Townships of Molin, Moorhead, and Oakport, and MnDOT District 4.

### Existing Conditions

1. 15<sup>th</sup> Ave N is currently a gravel township roadway.
2. Oakport, Moorhead, and Moland townships share jurisdiction of the roadway.
3. All townships contract with Clay County for blading and snow removal.
  - a. Townships are responsible for graveling operations.
  - b. Peyton M stated that Dilworth has a financial agreement with Oakport and Moorhead Townships to pay for 50% of maintenance operations.
  - c. Jeff W stated that the roadway is graveled about every three years.
4. Peyton M stated that the NE ¼ of 1-139-48 has been annexed by the City of Dilworth.
5. Veronica R discussed the existing traffic conditions throughout the corridor.
  - a. Traffic counts were collected using tubes and cameras
    - i. East of 50<sup>th</sup> St less than 100 vehicles per day
    - ii. Between CSAH 9 and 50<sup>th</sup> St there are about 300 vehicles per day
    - iii. Primary movements are eastbound to southbound and northbound to westbound at the 50<sup>th</sup> St intersection
    - iv. Traffic data shows that drivers are using 15<sup>th</sup> Ave N to cross the Red River but not as a thru route.



- b. Only 4 crashes were reported in recent crash data, all at the intersection of CSAH 9 and 15<sup>th</sup> Ave N.
    - i. No fatalities or serious injuries
    - ii. The only crash trend is winter weather related
    - iii. Not a critical crash rate location
  - c. There are no indications of speeding through the corridor.
- 6. There are existing utilities through the corridor:
  - a. City of Dilworth has a sanitary forcemain on the north side of the roadway from 34<sup>th</sup> St to 14<sup>th</sup> St NE.
  - b. There is a natural gas transmission line that crosses 15<sup>th</sup> Ave N approximately 1,200' east of CSAH 9.
  - c. There are overhead powerlines on the south side of Drain 41 with crossings throughout the corridor.
  - d. Based on KLJ's site visit and previous plans there are telecommunication lines on the north side of the corridor.
  - e. Jeff W stated that 702 Communications has a proposal to bury fiber along CSAH 11, but is not installed yet.

#### **Future Conditions**

- 1. Because of the low existing traffic volumes, KLJ is going to complete an origin-destination study to determine how many trips are generated from the north end of the metro area to TH 336/TH 10 and TH 336/I-94.
  - a. This will take into account future land use and growth rates
  - b. Future traffic volumes will be established based on this methodology.
- 2. Veronica R asked the group if there are any future improvements/developments in the next 10-15 years.
  - a. Michael M stated that MnDOT is currently conducting a study on I-94 to determine if a third lane in each direction should be added
  - b. TH 10 from 14<sup>th</sup> St (in Moorhead) through Dilworth will be reconstructed in the future.
  - c. Peyton M stated that Dilworth has purchased land in the NE ¼ of 2-139-48 and plans to construct a community park
    - i. Dilworth plans to extend 14<sup>th</sup> St NE to 15<sup>th</sup> Ave N in the future
    - ii. Metro COG is conducting a study to extend 8<sup>th</sup> Ave through Dilworth.
    - iii. Peyton M stated that it is anticipated that the N ½ of 2-139-48 and E ½ of the NW ¼ of 1-139-48 will be the future growth areas for Dilworth.
  - d. Peyton M stated that the city gets inquiries about the development for light industrial along the 34<sup>th</sup> St corridor.
    - i. Michael M stated that KLJ should reach out to Joe with the Greater FM EDC to see if they have any insights into development in the area.

#### **Known Issues**

- 1. Scott M asked the group if there were any known issues throughout the corridor.
  - a. Jeff W stated that trees in the NW corners of CSAH 9/15<sup>th</sup> Ave N, 50<sup>th</sup> St/15<sup>th</sup> Ave N, and NW corner of CSAH 11/15<sup>th</sup> Ave N can cause some sight distance issues.
  - b. Justin S stated that Clay County gets complaints about dust in the area and conditions of 15<sup>th</sup> Ave N between CSAH 9 and 50<sup>th</sup> St.
    - i. More blading is required in this section of the roadway.



- ii. Justin S stated that he feels the roadway would get used more if it was improved.
  - iii. Traffic counts tripled on 15<sup>th</sup> Ave N between 34<sup>th</sup> St and CSAH 9 after it was paved.
  - iv. Peyton M. stated complaints regarding the amount of dust were received over the course of force main and other improvements over the past few years.
- c. Jeff W stated that there is an underground aquifer that runs along CSAH 11 from south to North from Wolverton to Sabin. He stated that the Buffalo Red River Watershed District will know more about that.
- d. Jeff W stated that traveling along 15<sup>th</sup> Ave N approaching CSAH 11 it is unclear that the eastern leg is a residential driveway.

### **Public Involvement**

- 1. Scott M outlined the short-term public engagement strategy:
  - a. Public Awareness:
    - i. KLJ has a website set up with an interactive map to leave comments along with a survey for people to take.
    - ii. KLJ will have a booth at Loco Daze to introduce the public to the study and determine what the existing issues are on the corridor.
      - 1. Payton M stated that another good opportunity to get in front of the public could be Night to Unite on August 6. Michael M will consider attending to hand out postcards and increase survey participation.
    - iii. KLJ is planning for a pop-up event at a DGF football game in September.
  - b. Stakeholder Coordination:
    - i. KLJ is setting up meetings with various stakeholders such as:
      - 1. Dilworth Police
      - 2. Dilworth Fire
      - 3. Dilworth Maintenance
      - 4. Moorhead Engineering
      - 5. Buffalo Red River Watershed District
      - 6. Clay County Planning
      - 7. DGF School District Transportation
  - c. Landowner Engagement
    - i. KLJ has developed postcards to be mailed out to residents within 1,000 feet of the corridor to get their feedback.
      - 1. The postcards will have a QR code and website to direct landowners to the project website.
      - 2. KLJ contact information will be included if they would like to discuss the study.

### **Next Steps**

- 1. KLJ will prepare the existing conditions/future conditions report and submit it to the SRC for review.
- 2. Scott M will send out an invite for SRC Meeting #2 on August 26



# Study Review Committee #1

July 22, 2024






# Agenda

- Introductions
- Study Overview
- Existing/Future Conditions
- Known Issues
- Public Involvement
- Going Forward




# Study Overview





# Existing Conditions




**15<sup>th</sup>** Ave N  
Corridor Study

**METROCOG**  
FM REGIONAL TRANSPORTATION PLANNING ORGANIZATION



# Traffic Volumes



Volumes listed as AM Peak (PM Peak)

AM Peak is 7-8 AM


PM Peak is 4:30-5:30 PM



# Future Conditions Methodology

Three types of volumes being added to the corridor:

- Background growth rate
- Land use change
- Traffic diversion from I-94, US 10 & 28<sup>th</sup> Avenue





# Crash Data

## Crash 1

- September 2017
- No Injury
- Angle Crash
- Rain, Wet Road

## Crash 2

- December 2019
- Possible Injury
- Angle Crash
- Icy Road, Slid through Intersection

## Crash 3

- October 2023
- No Injury
- Angle Crash
- Unable to Stop

## Crash 4

- December 2023
- No Injury
- Run Off Road
- Distracted Driver

All crashes occurred near one intersection:  
15<sup>th</sup> Avenue & CSAH 9





# Utilities

## Natural Gas

Crosses 15<sup>th</sup> Ave underground between 40<sup>th</sup> St and 50<sup>th</sup> St

## Overhead Power

Runs along south side of 15<sup>th</sup> Ave from 40<sup>th</sup> St to 70<sup>th</sup> St

Crosses 15<sup>th</sup> Ave to access substation at 50<sup>th</sup> St

## Sanitary Forcemain

Along north side of 15<sup>th</sup> Ave from 40<sup>th</sup> St past 50<sup>th</sup> St subdevelopment

Branch lines cross 15<sup>th</sup> Ave





# Know Corridor Issues?

Open Discussion





# Public Involvement

- Loco Daze
  - Introduction to Project
  - Existing Conditions Map
  - Project Survey
- Stakeholder Meetings
  - Discuss known corridor issues
- Landowner Engagement
  - Post Card
  - Project Survey



# Going Forward

- Loco Daze Public Engagement
- Future Conditions
- Existing Conditions/Future Conditions Report
- SRC Meeting #2 – Targeting week of 8/26
  - Stakeholder Recap
  - Future Conditions Review
  - Alternative Development Kickoff





# 15<sup>th</sup> Avenue N Corridor Study – SRC Meeting #2

## Meeting Minutes

**Date:** 8/26/2024

**Time:** 11:00 AM

**Facilitator:** Scott Middaugh

**Attendees:** Michael Maddox – Metro COG; Justin Sorum – Clay County; Peyton Mastera, Don Lorsung, Matthew Engbrecht – City of Dilworth; Mary Safgren – MnDOT; Carol Kurtyka – Moorhead Township; Jerry Gee – Oakport Township; Todd Hummel, Veroncia Richfield, Scott Middaugh - KLJ

### Introductions

1. Introduction for the group were made. Representatives from Moland Township were not present.

### Public Involvement

1. Scott M. gave an overview of the public involvement that has been completed to date:
  - a. KLJ staff attended Loco Daze to introduce the public to the project and directed them to the project website and project survey.
  - b. Postcards were mailed to landowners within 1,000' of the corridor to inform them of the study and direct them to the project survey.
2. Scott M. reviewed the results of the project survey as of 8/19/24
  - a. To date 118 people have participated in the survey.
3. Scott M. asked the group if it was ok to close the survey as another round of public engagement will be completed later this fall.
  - a. No opposition from the group.
4. Scott M. stated that two individuals along the corridor have reached out via email or phone to voice their opinion about the project
  - a. One individual was strongly opposed to the project
  - b. One individual was not opposed to the project but was opposed to losing a portion of their land for roadway improvements.

### Existing Traffic Volumes Recap

1. Veronica R. gave an overview of the existing traffic volumes collected on the corridor.
  - a. A combination of cameras and tube counters were used to collect the existing traffic data.
2. Scott M. stated that this information is available in the Existing and Future Conditions report that was sent out to the group last week.
  - a. Scott M. requested that all comments on the report be received by 9/4/24.

### Future Conditions

1. Veronica R. gave an overview of the methodology used to determine future traffic volumes for the corridor.
  - a. Three components used to determine future traffic volumes:
    - i. Background growth rate – observed through the entire metro area
    - ii. Traffic diversion based on an origin-destination analysis – determining what percent of traffic will divert from 28<sup>th</sup> Ave, US 10, and I-94 if the corridor is improved



- iii. New development in the area – looking at different development scenarios within Dilworth and adjacent to the corridor
2. Three scenarios were reviewed based on different ranges of the three components listed above:
  - a. Low Increase – 2045 ADT of 500 to 2,700 along 15<sup>th</sup> Ave N
  - b. Moderate Increase – 2045 ADT of 780 to 3,000 along 15<sup>th</sup> Ave N
  - c. High Build-Out Increase – 2045 ADT of 1,350 to 7,700 along 15<sup>th</sup> Ave N
3. Veronica R. discussed possible new intersections with the corridor and the amount of traffic those intersections could generate based on the development adjacent to the corridor.
4. Based on the model results the corridor and its intersections operate at an acceptable level of service (LOS) if:
  - a. On the moderate increase scenario, the two-way stop at CSAH 9/15<sup>th</sup> Ave N is swapped from an E/W stop control to a N/S stop control
  - b. On the high build-out scenario CSAH 9 would need improved intersection control such as a roundabout to operate at LOS C
5. Don L. asked if traffic that would permanently use 15<sup>th</sup> Ave N in the future was considered in the analysis.
  - a. Veronica R. stated that was incorporated as part of the origin-destination analysis.
6. Michael M. asked what the probability of meeting the high build-out traffic volumes was.
  - a. Scott M. stated it wasn't too likely, but it was more of an exercise to determine if the area sees significant development would it create traffic volumes that would require a different roadway section than the lower scenario traffic forecasts.

#### **Alternatives Development**

1. Scott M. stated that the alternatives that have been developed are very high level and are to for the group to review and determine if there are any alternatives that shouldn't be carried forward or if there are any alternatives beyond what we present that should be considered.
2. Todd H. walked through the existing typical section and the proposed typical sections:
  - a. Rural two lane
    - i. 12' lanes with 1' shoulders
    - ii. 12' lanes with 8' shoulders
      1. Either fully paved or just 2' of the 8' paved
  - b. Urban two lane
    - i. 12' lanes with curb and gutter
  - c. Pedestrian facilities
    - i. Heartland Trail study includes an alternative to follow 15<sup>th</sup> Ave N
    - ii. Alternatives could include a 10' sidewalk on either the north or south side of the roadway
  - d. Todd H. stated that Drain 41 has 1:4 inslopes on the north side so it would be a safe slope adjacent to the roadway
    - i. Would need to discuss the clear zone with the group as the water level in the drain varies throughout the year
      1. Michael M. asked what clear zone we were using at the moment
        - a. Scott M. stated that we haven't determined the clear zone as it will vary depending on design speed.
  - e. Peyton M. stated that he feels that curb and gutter on this roadway feels excessive.



- f. City of Dilworth stated that pedestrian facilities should be included, maybe not on the eastern mile of the study area, but it would be good to have an east/west connection to Moorhead.
- 3. Scott M. stated that before the alternatives analysis can get too far, the group will need to meet and discuss future ownership and maintenance of the roadway. For example, standards for County design may require a different typical section than if the townships or City of Dilworth would own the roadway.
  - a. Michael M. agreed that future ownership needs to be determined as the lane width could be reduced to 11' depending on ownership.

#### **Next Steps**

- 1. Scott M. stated that the next steps of for KLJ to continue the Alternative Development, which will have to work in tandem with the Implementation Plan.
  - a. Scott M. will be sending out a Doodle Poll to determine what time works best for the group to meet in person
    - i. Peyton M. and Justin S. stated that they both have conference rooms that could host the meeting.
    - ii. It was determined that the City of Dilworth, Clay County, and all townships should be involved in the meeting.
      - 1. Mary S. stated that MnDOT feels this should be a local road and does not need to be part of this meeting.
- 2. Scott M. stated that the next SRC meeting is scheduled for the week of 10/13.
  - a. Justin S. said that Monday 10/14 at 11 seems to work for the group
  - b. Don L. asked if the meeting could be on Wednesday, 10/16.
    - i. Scott M. will send out a Doodle Poll to see who is available between the two times.



# Study Review Committee #2

August 26, 2024





# Agenda

- Introductions
- Public Involvement
- Existing Traffic Volumes Recap
- Future Conditions
- Alternatives Analysis Kickoff
- Next Steps




# Public Involvement

- Attended Loco Daze
  - Introduced project
  - Directed public to survey
- Post cards
  - 1000' radius around project
  - Informed residents/landowners of project
  - Directed to project survey




# Survey Results (as of 8/19/24)

Do you live, own, or rent property along the corridor?




How do you currently use the corridor?






# Survey Results (as of 8/19/24)

How frequently do you use the corridor?



■ Daily ■ 2-4 times per week ■ Less than once per week ■ I don't use the corridor

Would you use the corridor if it was improved beyond a gravel roadway?




■ Yes ■ No




# Survey Results (as of 8/19/24)

Would future improvements interfere with how you currently use the corridor?



■ Yes ■ No

What would you like the roadway to include in the future?




- Paved urban roadway (includes curb and gutter)
- Paved rural roadway (does not include curb and gutter)
- Widened and improved gravel roadway
- Bike/pedestrian sidewalk or trail
- I do not want to see the roadway improved from its current condition
- Other



# Survey Results (as of 8/19/24)

Where do you live?






# Survey Results (as of 8/19/24)

## Survey Comment Box

- Common Themes
  - Excessive speeds
  - Add pedestrian facilities
  - Project costs/special assessments


Public Comments



■ In Favor ■ Against ■ Neutral



# Existing Traffic Volumes Recap



Volumes listed as AM Peak (PM Peak)

AM Peak is 7-8 AM

PM Peak is 4:30-5:30 PM



# Future Conditions Methodology

Three components for future volumes:

(1) Background growth rate – (2) Traffic diversion (from O/D) – (3) New development

Scenario	Background Growth Rate	Diverted Traffic	Development Level
Low Increase	0.5%	Minimal	2045 Comprehensive Plan
Moderate Increase	1.0%	Expected	2045 Comprehensive Plan
High Build Out	1.5%	Increased	Expanded




# Future Volumes – Diverted Traffic

StreetLight Origin-Destination (Top Routes) Analysis:

- Drivers traveling between north Fargo and east of the metro may opt to reroute along an improved 15th Ave
- Rerouting potential is highest along three routes: I-94, US 10, 28<sup>th</sup> Ave

Scenario	Proportion of North Fargo-East Metro Traffic Diverted		
	I-94	US 10	28th Avenue
Low Increase	0%	10%	25%
Moderate Increase	10%	35%	50%
High Build Out	10%	35%	100%

**15<sup>th</sup> Ave N**  
Corridor Study





# Future Volumes – New Developments

	New Trips Generated (Per Day, 2045)				
Scenario	Light Industrial	Single Family Housing	Multifamily Housing	Public Park	Commercial/ Retail
Low/Moderate Increase	390	1,266	454	140	0
High Build Out	390	3,165	1,135	140	1,906


*Source: Institute of Transportation Engineers TripGen*



# Future Road Considerations

New roads may be constructed to connect future development:

- Between 40<sup>th</sup> & 50<sup>th</sup>
- Between 50<sup>th</sup> & 60<sup>th</sup>



*New roads not modeled in Future Level of Service analysis.*



# Future Volumes (2045)

Low Increase Scenario





# Future Volumes (2045) [Continued]

Moderate Increase Scenario





# Future Volumes (2045) [Continued]

High Build-Out Scenario





# Model Results

	Future (2045) Delay	Mitigation Warranted	Mitigation Type
Existing	Acceptable	No	-
Low Increase Scenario	Acceptable	No	-
Moderate Increase Scenario	Acceptable	No, but improves operations	Switch the stop-controlled approaches: CSAH 9 stops
High Build Out Scenario	Unacceptable	Yes	<b>Roundabout</b> at CSAH 9




# Alternatives Development

- Rural 2 Lane
- Urban 2 Lane
- Pedestrian Facilities
  - North Side
  - South Side
  - Heartland Trail Incorporation



# Existing Section


- Land Acquisition
- Tree Impacts



- BRRWD Drain 41
- Clearzone Requirements
  - Edge of Driving Lane




# Rural 2 Lane (Matching West of CSAH 9)






# Rural 2 Lane with Gravel Shoulders






# Rural 2 Lane with Paved Shoulders






# Rural Section with Path on North






# Rural Section with Path on South



- Shoulder, Boulevard, & Path included in Clearzone




# Urban 2 Lane with Path on North



- Likely Storm Sewer



# Urban 2 Lane with Path on South



- Storm Sewer Required

- Shoulder, Curb, Boulevard, & Path included in Clearzone



# Next Steps

- Refine Alternatives & Scoring Criteria
- Begin Implementation Plan Development
- SRC #3 Planned for week of October 13<sup>th</sup>





# 15<sup>th</sup> Avenue N Corridor Study – SRC Meeting #3

## Meeting Minutes

**Date:** 10/14/2024

**Time:** 11:00 AM

**Facilitator:** Scott Middaugh

**Attendees:** Michael Maddox – Metro COG; Justin Sorum – Clay County; Peyton Mastera, Matthew Engbrecht – City of Dilworth; Mary Safgren – MnDOT; Carol Kurtyka – Moorhead Township; Jerry Gee – Oakport Township; Jeff Winter – Moland Township; Todd Hummel, Scott Middaugh - KLJ

### Alternatives Analysis

1. Todd H. gave an overview of the alternatives. Five typical sections have been developed:
  - a. Rural Minimum – 2' shoulders, 11' driving lanes
  - b. Rural Non-CSAH County Minimum – 4' shoulders, 11' driving lanes
  - c. Rural CSAH County Minimum – 8' shoulders, 11' driving lanes
  - d. Urban Option 1 – curb & gutter, 36' flow line to flow line of gutter
  - e. Urban Option 2 – curb & gutter, 40' flow line to flow line of gutter
2. Based on the Future Ownership & Maintenance meeting held on 10/7 alternatives a & b above will be carried forward
3. There are options for each typical section to include a separate pedestrian path on the south side of the roadway
  - a. The inclusion of a pedestrian path adds approximately 18' of right of way acquisition to the alternatives
4. Based on Northside Park Addition (south side of 15<sup>th</sup> Ave between CSAH 9 and 50<sup>th</sup> St) and the Summerwood Addition (south side of 15<sup>th</sup> Ave between 50<sup>th</sup> St to just east of 50<sup>th</sup> St) the design team assumed 50' minimum right of way acquisition north of the proposed centerline.
5. Because of Drain 41 paralleling the south side of 15<sup>th</sup> Ave, any widening for the roadway will need to be shifted to the north.
  - a. There are two residential properties and a power pole guy wire at the substation that would be impacted by shifting the roadway north
6. When shifting the roadway north, the design team held the hinge point where the top of roadway breaks and the inslope of the drain begins.
7. Todd H. summarized the right of way needs for the different typical sections with and without a separate pedestrian path.
8. If the roadway is shifted north, the residential properties at the NE corner of 15<sup>th</sup> Ave/CSAH 9 and the NE corner of 15<sup>th</sup> Ave/60<sup>th</sup> St will be impacted
  - a. Both of those property owners have reached out and expressed resistance to property impacts
  - b. Justin S has stated that snow drifting has been an issue at the NE corner of 15<sup>th</sup> Ave/CSAH 9 because the trees are directly adjacent to the north side of the road
9. Michael M asked if turn lanes are required anywhere. Scott M stated that KLJ has ran the analysis and determined that some turn lanes are required, but not at all locations. The turn lanes will be incorporated into the alternative exhibits
10. In an effort to avoid residential property impacts, the design team has looked at shifting the roadway to the south at the NE corner of 15<sup>th</sup> Ave/CSAH 9 and the NE corner of 15<sup>th</sup> Ave/60<sup>th</sup> St
  - a. This shift would require shifting Drain 41 and the overhead powerlines.



- b. If separate pedestrian facilities are included, the further the drain will have to shift
  - c. The existing 33' right of way would be the northern edge of the corridor, everything would shift south from there
  - d. KLJ has discussed a drain shift with the Buffalo-Red River Watershed District (BRRWD) and they weren't opposed, but there is a process that needs to be followed
    - i. Scott M will follow up with BRRWD to confirm nothing has changed
- 11. Todd H summarized the right of way needs for the different typical sections with and without a separate pedestrian path if the roadway was shifted to the south
  - a. The right of way impacts are based on a 40 MPH curve design speed
  - b. Justin S stated that if the roadway is owned by Clay County they may have to design to 55 MPH
    - i. Justin said he would be fine if the roadway was signed at 55 MPH but the curves had an advisory sign of 40 MPH
- 12. Todd H reviewed the requirements for on and off road bike facilities in urban and rural conditions
- 13. Scott M updated the group with the latest on the Heartland Trail study and how it pertains to the 15<sup>th</sup> Ave project
  - a. KLJ is met with the Heartland Trail study team on Tuesday (10/15) to discuss the two projects
  - b. Currently, the preferred alignment for the trail is to enter Dilworth/Moorhead at the intersection of 12<sup>th</sup> Ave S/34<sup>th</sup> St, then follow 34<sup>th</sup> St N to 15<sup>th</sup> Ave N, then follow 15<sup>th</sup> Ave to Centennial Park
    - i. This alignment was selected to avoid crossing the railroad at Main St in Dilworth
  - c. In the future, when an overpass is constructed at 14<sup>th</sup> St in Dilworth, the trail will enter Dilworth at the intersection of 12<sup>th</sup> Ave S/14<sup>th</sup> St, head north along 14<sup>th</sup> St to 15<sup>th</sup> Ave N, then parallel 15<sup>th</sup> Ave N to Centennial Park in Moorhead
  - d. The Heartland Trail team is going to look at the possibility of locating the trail on the south side of the drain to minimize right of way impacts for 15<sup>th</sup> Ave N on the north side of the drain.
- 14. The following questions were asked of the group:
  - a. Should alternatives include options for pedestrian facilities?
    - i. Peyton M stated that they should between CSAH 9 and 60<sup>th</sup> St
  - b. How much right of way should be preserved on the corridor?
    - i. The group concurred with the 50' assumed by the design team
  - c. Should right of way be preserved for future rural to urban improvements?
    - i. Peyton M stated that right of way should be acquired for Urban Option 1
    - ii. Peyton M requested that KLJ contact Moore Engineering to coordinate with future city infrastructure
  - d. Should options include realigning the roadway/ditch to the south to avoid residential property impacts on the north side of 15<sup>th</sup> Ave?
    - i. Peyton M stated he did not think it was necessary due to costs
    - ii. Michael M stated that with the NEPA process, costs cannot be a factor in determining alternatives, therefore the alignment shift should be included
- 15. Todd H summarized the scoring criteria that will be used to score the alternatives. The corridor study will not recommend a preferred alternative but instead can rely on scoring metrics to see what alternative scores the best



16. Scott M stated that KLJ will get going on the design alternatives and send out to the group for approval.
  - a. The next step in this process will be to go to the public with our findings of the study
  - b. Scott M asked if we needed to have the future ownership/maintenance clarified prior to the public input meeting.
    - i. Peyton M stated that he didn't feel a conclusion was necessary for the public input meeting, but could be discussed as a general topic
  - c. Peyton M stated that the public input meeting could be held at Dilworth's Depot Facility



# Study Review Committee #3

October 14, 2024





# Agenda

Alternatives Analysis Refinement

Alternative Scoring Criteria

Future Public Involvement

Next Steps



# Alternatives Development

Rural Minimum (Industry Standards)

Rural Minimum (Non CSAH)

Rural State Aid (CSAH)


Urban Option 1 (36' face to face)

Urban Option 2 (40' face to face)

- Pedestrian Facilities/ Shared Use Paths Options
- Realignment Options




# Alternatives Development






# Rural Minimum (Industry Standards)






# Rural Minimum (Non CSAH)






# Rural State Aid (CSAH)






# Urban Option 1





# Urban Option 2






# Proposed Right of Way Summary

	Rural Minimum		Rural Minimum		Rural State Aid		Urban Option 1		Urban Option 2	
	(Industry Standards Approved by State Aid Engineer)		(Non CSAH)		(CSAH)					
	11' Driving Lanes w/2' Shoulder		11' Driving Lanes w/4' Shoulder		11' Driving Lanes w/8' Shoulder		36' Face to Face		40' Face to Face	
	w/o SUP	w/ SUP	w/o SUP	w/ SUP	w/o SUP	w/ SUP	w/o SUP	w/ SUP	w/o SUP	w/ SUP
Alignment Shift (FT to North)	1'	19'	3'	21'	7'	25'	13'	25'	15'	27'
Additional ROW (FT to North)	18'	36'	20'	38'	24'	42'	30'	42'	32'	44'
Additional ROW (Acres)	6.55	13.09	7.27	13.82	8.73	15.27	10.91	15.27	11.64	16




# Proposed Right of Way

↑↑ 40<sup>th</sup> Street





# Proposed Right of Way



RURAL 4' SHLDR

RURAL 4' SHLDR W/ SUP

RURAL 8' SHLDR

RURAL 8' SHLDR W/ SUP

URBAN 36'


URBAN 36' W/ SUP

URBAN 40'

URBAN 40' W/ SUP




# Realignment at Residential Properties





# Realignment at Residential Properties






# Realignment at Residential Properties


~750' + Transitions

↑↑  
40<sup>th</sup> Street  
↑↑





# Realignment at Residential Properties







# Proposed Right of Way Summary

	Rural Minimum		Rural Minimum		Rural State Aid		Urban Option 1		Urban Option 2	
	(Industry Standards)		(Non CSAH)		(CSAH)					
	11' Driving Lanes w/2' Shoulder		11' Driving Lanes w/4' Shoulder		11' Driving Lanes w/8' Shoulder		36' Face to Face		40' Face to Face	
	w/o SUP	w/ SUP	w/o SUP	w/ SUP	w/o SUP	w/ SUP	w/o SUP	w/ SUP	w/o SUP	w/ SUP
Alignment Shift (FT to South)	17'	17'	17'	17'	17'	17'	17'	17'	17'	17'
Drain 41 Shift (FT to South)	18'	36'	20'	38'	24'	42'	30'	42'	32'	44'
Approximate Drain 41 Realignment Length (40 MPH Curve)	3,818'	4,882'	3,954'	4,978'						



# Pedestrian Facilities






# Pedestrian Facilities

For roadways which are being reconstructed or retrofitted where preferred Green Book shoulder widths cannot be provided, designers should provide the recommended shoulder width shown in Figure 10. Where those recommended widths cannot be provided, the following minimum paved shoulder widths can provide a minimum level of bicycle accommodation:

- A shoulder width of at least 3 feet on open-section roadways with no vertical obstructions immediately adjacent to the roadway and no rumble strips.
- A shoulder width of at least 5 feet is recommended from the face of a guardrail, curb, or other roadside barrier to provide additional operating width, as bicyclists generally shy away from a vertical face.

Increasing the width of shoulders is preferable where higher bicycle usage is expected and if motor vehicle speeds exceed 45 mph; if use by heavy trucks, buses, or recreational vehicles exceeds 5% of ADT; or if obstructions exist along the roadside.





# Alternatives Questions

Should alternatives include options for pedestrian facilities?

If including pedestrian facility options, what are the extents?  
(40<sup>th</sup> to 50<sup>th</sup>, 40<sup>th</sup> to 60<sup>th</sup>, or 40<sup>th</sup> to 70<sup>th</sup>/entire corridor?)

How much right of way should be preserved on the corridor?

Should the right of way be preserved for future improvements?  
(i.e. rural alternatives, but with the ROW for urban alternatives)

Should the options include realigning to avoid property impacts?

## Rural Minimum (Industry Standards)

### On Alignment

- w/o Shared Use Path
- w/ Shared Use Path

### Realignment

- w/o Shared Use Path
- w/ Shared Use Path

## Rural Minimum (Non CSAH)

### On Alignment

- w/o Shared Use Path
- w/ Shared Use Path

### Realignment

- w/o Shared Use Path
- w/ Shared Use Path



# Scoring Criteria

Pedestrian Facilities

Right of Way

Drain 41 Impacts

Residential Property Impacts

Utility Impacts

Environmental and Cultural Impacts

Project Costs



## Pedestrian Facilities

**No Pedestrian Facilities**

**On Street Facilities**

**Separated Facilities**

**Little/No Benefit**

**Some Benefit**

**Greatest Benefit**

Does the alternative provide safe, comfortable, and accessible bicycle and pedestrian facilities?



## Right of Way

Most Right of Way

Least Right of Way

Little/No Benefit

Some Benefit

Greatest Benefit

Does the alternative require temporary or permanent right of way?



## Drain 41 Impacts

**Most Drain 41 Impacts**

**Some Drain 41 Impacts**

**No Drain 41 Impacts**

**Little/No Benefit**

**Some Benefit**

**Greatest Benefit**

Does the alternative require impact Drain 41?



## Residential Property Impacts

**Most Residential  
Property Impacts**

**Least Residential  
Property Impacts**

**Little/No Benefit**

**Some Benefit**

**Greatest Benefit**

Does the alternative impact the existing residential properties adjacent to the project corridor?



## Utility Impacts

**Most Utility Impacts**

**Least Utility Impacts**

**Little/No Benefit**

**Some Benefit**

**Greatest Benefit**

Does the alternative impact any existing private utilities?



## Environmental & Cultural Impacts

**Most Environmental &  
Cultural Impacts**

**Least Environmental &  
Cultural Impacts**

**Little/No Benefit**

**Some Benefit**

**Greatest Benefit**

Does the alternative impact any existing environmental resources?



## Project Costs

Highest Project Costs

Lowest Project Costs

Little/No Benefit

Some Benefit

Greatest Benefit

What is the approximate project construction cost for each alternative?



# Public Involvement

- Public Input Meeting
  - Originally Proposed for mid-October
- Does SRC want Ownership/Maintenance discussed?
- Topics to Discuss
  - Existing Conditions
  - Phase I Feedback
  - Alternatives
  - Scoring
  - Survey





# 15<sup>th</sup> Avenue N Corridor Study – SRC Meeting #4

## Meeting Minutes

**Date:** 12/18/2024

**Time:** 11:00 AM

**Facilitator:** Scott Middaugh

**Attendees:** Michael Maddox – Metro COG; Peyton Mastera, Don Lorsung – City of Dilworth; Mary Safgren – MnDOT; Carol Kurtyka – Moorhead Township; Jerry Gee – Oakport Township; Jeff Winter – Moland Township; Todd Hummel, Scott Middaugh, Wade Kline - KLJ

### Alternatives Analysis

1. Scott M stated that the Alternatives Analysis was submitted to the SRC for review and comment. Only one comment has been received so far.
2. Scott M recapped the Alternatives Analysis report:
  - a. Alternatives considered but dismissed
    - i. Urban sections using City of Dilworth standards – dismissed due to cost, and does not align with near term usage and ownership of the corridor
    - ii. Clay County CSAH – dismissed because Clay County does not have any CSAH miles available for this corridor and does not want to remove miles from any other CSAH route to apply to this corridor
  - b. Alternatives Presented at Public Input Meeting
    - i. Rural Minimum Industry Standards (Typical Section 2)
      1. 11' driving lanes, 2' shoulders (the same section recently constructed west of the corridor)
      2. \$7-8 million in construction costs
      3. 6.61 acres of ROW
    - ii. Rural Minimum Industry Standards with Path (Typical Section 3)
      1. 11' driving lanes, 2' shoulders, 10' shared use path
      2. \$8-9 million in construction costs
      3. 10.18 acres of ROW
    - iii. Clay County Minimum Standards (Typical Section 4)
      1. 11' driving lanes, 4' shoulders
      2. \$9-10 million in construction costs
      3. 8.93 acres of ROW
    - iv. Clay County Minimum Standards Path (Typical Section 5)
      1. 11' driving lanes, 4' shoulders, 10' shared use path
      2. \$10-11 million in construction costs
      3. 12.65 acres of ROW
    - v. Clay County Minimum Standards with Southern Alignment Shift (Typical Section 6)
      1. 11' driving lanes, 4' shoulders, realigned to avoid residential impacts north of 15<sup>th</sup> Ave
      2. \$10.5-11.5 million in construction costs
      3. 10.73 acres of ROW
    - vi. Clay County Minimum Standards with Southern Alignment Shift with Path (Typical Section 7)



1. 11' driving lanes, 4' shoulders, realigned to avoid residential impacts north of 15th Ave, 10' shared use path
    2. \$11.5-12.5 million in construction costs
    3. 13.25 acres of ROW
  - vii. Don L asked why ROW is shown as a need for the Rural Minimum Industry Standard. The project that was constructed in 2019 just to the west did not require any ROW.
    1. Scott M stated that the existing project didn't acquire ROW but utilized the existing 17' sanitary sewer easement for grading. KLJ showed ROW as a need to make sure that was clear in the report.
3. Scott M reviewed the scoring matrix and the categories that were used to score the different alternatives:
  - a. Right of Way Acquisition
  - b. Roadway Reliability
  - c. Residential Property Impacts
  - d. Meets Purpose & Need
  - e. Pedestrian Mobility
  - f. Construction Costs
4. Scott M stated that the Public Input meeting for the project was held on November 21, 2024 from 5-7 at the Dilworth Depot Facility
  - a. Legal ads, press release, direct post card mailings, and social media posts were used to advertise the meeting
  - b. 16 people attended in person, 60 online surveys completed
5. Scott M reviewed the survey results
  - a. Question 1: Please rank the following metrics in order from most important to least important:
    - i. Roadway Reliability
    - ii. Meets Purpose & Need
    - iii. Cost
    - iv. Residential Property Impacts
    - v. Pedestrian Mobility
    - vi. Right of Way Acquisition
  - b. Question 2 (online results): What is your preferred alternative:
    - i. Clay County Minimum with Path (Typical Section 5)
    - ii. Rural Minimum Industry Standard with Path (Typical Section 3)
    - iii. Clay County Minimum (Typical Section 4)
    - iv. Clay County Minimum with Southern Alignment Shift and Path (Typical Section 7)
    - v. Rural Minimum Industry Standard (Typical Section 2)
    - vi. No Build (Typical Section 1)
    - vii. Clay County Minimum with Southern Alignment Shift (Typical Section 6)
  - c. Question 2 (in person results): What is your preferred alternative:
    - i. Clay County Minimum (Typical Section 4)
    - ii. Clay County Minimum with Southern Alignment Shift and Path (Typical Section 7)
    - iii. Clay County Minimum with Path (Typical Section 5)



- iv. Clay County Minimum with Southern Alignment Shift (Typical Section 6)
    - v. No Build (Typical Section 1)
  - d. Question 3: Where do you live:
    - i. Dilworth, MN
    - ii. Moorhead, MN
    - iii. None of the above
    - iv. Do not wish to say
  - e. Jeff W asked who initiated this project.
    - i. Scott M stated that during the US 10 Corridor Study it was identified that that additional east/west corridors were needed through the metro area. Metro COG lead that corridor study and is the lead agency for this corridor study
    - ii. Jeff W asked what is Metro COG and who funds that
      - 1. Michael M stated that Metro COG is the metropolitan planning organization for Fargo-Moorhead area. They represent Fargo, Moorhead, West Fargo, Dilworth, Horace, Clay County, and Cass County. They are funded by NDDOT and MnDOT.
    - iii. Peyton M stated that from Dilworth City limits encompass all parts of the roadway that Moorhead Township maintains.
    - iv. Peyton M stated that Dilworth is working with Metro COG to obligate approximately \$1M of STBG funding to 15<sup>th</sup> Ave between CSAH 9 and 50<sup>th</sup> St in 2029.
- 6. Wade K discussed the draft Implementation Plan
  - a. Wade recommended that a memorandum of understanding that will outline a forum for corridor preservation, regular communication with stakeholders and public, and describe cost sharing be established. Wade echoed that there is funding available already for 2029 construction.
  - b. Wade described that the timing and phasing for this project will likely happen based on funding, but would generally be constructed from east to west, targeting that the entire roadway be paved by 2030.
  - c. Wade discussed ownership and that the County has been a great steward for this corridor. Wade further stated that the County should likely be the short term owner that manages this corridor with cost sharing identified through an MOU. Local funding would also be identified through an MOU. Lastly, there could be LRIP funding that could be obtained in the next solicitation in the Fall of 2025
  - d. Wade K stated that functional classification would be key in obtaining federal funding. Some of those federal funding sources could be the Surface Transportation Block Grant Program STPBG through Metro COG (already secured) and the Carbon Reduction Program (linked to the TH 10 relief/ construction).
  - e. Jeff W asked if the City of Moorhead has been involved in the study and if they have any concerns with the increased traffic
    - i. Scott M stated that KLJ coordinated with the City of Moorhead early in the process. Moorhead realizes that traffic on 15<sup>th</sup> will continue to increase over time. They don't have any concerns about roadway capacity within the City of Moorhead and they did not indicate any new traffic control improvements at the intersection of 34<sup>th</sup> St/15<sup>th</sup> Ave



- f. Michael M stated that the County has expressed concerns about not having long term ownership of this roadway and attempting to identify any metrics as to when the ownership would then transition to the City of Dilworth. Sco stated that it has been discussed, but that we have not yet identified any metrics that would be adequate with the numerous unknowns. Wade stated that it's difficult to transition the ownership back to the City through metrics because the City would need to have both sides of the corridor within the City limits.
- g. Wade K asked who the recipient of the federal funding would be if the County would not be the owner.
  - i. Michael M said the County or the City would need to be, however, the City may take the Federal funding for the first mile, and potentially the remaining sections of the corridor would need to go through the County.
- h. Michael M stated that when US 10 through Dilworth is reconstructed by MnDOT traffic on 15<sup>th</sup> Ave will increase. It may be worth looking at the option to pave 60<sup>th</sup> St from US 10 to 15<sup>th</sup> Ave and 15<sup>th</sup> Ave from 60<sup>th</sup> St to CSAH 9. This could possibly eliminate the need to pave 15<sup>th</sup> Ave from 60<sup>th</sup> St to CSAH 11.



# Study Review Committee #4

December 18, 2024





# Agenda

Alternatives Analysis

Public Input Results

Implementation Plan

Next Steps




# Alternatives Analysis

- Alternatives Consider but Dismissed
  - Rural CSAH Standards
    - Reason: Costly standards, not likely to be a CSAH
  - Dilworth Urban Section
    - Reason: Costly requirements and projected ownership in the short term



# Alternatives Analysis


- \$7M to \$8M
- 6.61 Acres of ROW





# Alternatives Analysis


- \$8M to \$9M
- 10.18 Acres of ROW





# Alternatives Analysis


- \$9M to \$10M
- 8.93 Acres of ROW





# Alternatives Analysis


- \$10M to \$11M
- 12.65 Acres of ROW





# Alternatives Analysis


- \$10.5M to \$11.5M
- 10.73 Acres of ROW





# Alternatives Analysis

- \$11.5M to \$12.5M
- 13.25 Acres of ROW





# Alternative Scoring

Right of Way Acquisition	Most Right of Way Little to No Benefit	Least Right of Way Greatest Benefit
Alternative 1: No Build	— — — — —	●
Alternative 2: Rural Minimum Industry Standards	— — — — —	●
Alternative 3: Rural Minimum Industry Standards with Path	— — — ●	
Alternative 4: Clay County Minimum	— — — — ●	
Alternative 5: Clay County Minimum with Path	— ●	
Alternative 6: Clay County Minimum with Southern Alignment Shift	— — — ●	
Alternative 7: Clay County Minimum with Path & Southern Alignment Shift	●	

Residential Property Impacts	Most Property Impacts Little to No Benefit	Least Property Impacts Greatest Benefit
Alternative 1: No Build	— — — — —	●
Alternative 2: Rural Minimum Industry Standards	— — — — —	●
Alternative 3: Rural Minimum Industry Standards with Path	— — ●	
Alternative 4: Clay County Minimum	— — — — ●	
Alternative 5: Clay County Minimum with Path	●	
Alternative 6: Clay County Minimum with Southern Alignment Shift	— — — — —	●
Alternative 7: Clay County Minimum with Path & Southern Alignment Shift	— — — — —	●

Pedestrian Mobility	Least Pedestrian Mobility Little to No Benefit	Most Pedestrian Mobility Greatest Benefit
Alternative 1: No Build	●	
Alternative 2: Rural Minimum Industry Standards	— ●	
Alternative 3: Rural Minimum Industry Standards with Path	— — — — —	●
Alternative 4: Clay County Minimum	— — ●	
Alternative 5: Clay County Minimum with Path	— — — — —	●
Alternative 6: Clay County Minimum with Southern Alignment Shift	— — ●	
Alternative 7: Clay County Minimum with Path & Southern Alignment Shift	— — — — —	●

Roadway Reliability	Least Roadway Reliability Little to No Benefit	Most Roadway Reliability Greatest Benefit
Alternative 1: No Build	●	
Alternative 2: Rural Minimum Industry Standards	— — — — —	●
Alternative 3: Rural Minimum Industry Standards with Path	— — — — —	●
Alternative 4: Clay County Minimum	— — — — —	●
Alternative 5: Clay County Minimum with Path	— — — — —	●
Alternative 6: Clay County Minimum with Southern Alignment Shift	— — — — —	●
Alternative 7: Clay County Minimum with Path & Southern Alignment Shift	— — — — —	●

Purpose & Need (P&N)	Does Not Meet P&N Little to No Benefit	Meets P&N Greatest Benefit
Alternative 1: No Build	●	
Alternative 2: Rural Minimum Industry Standards	— — — — —	●
Alternative 3: Rural Minimum Industry Standards with Path	— — — — —	●
Alternative 4: Clay County Minimum	— — — — —	●
Alternative 5: Clay County Minimum with Path	— — — — —	●
Alternative 6: Clay County Minimum with Southern Alignment Shift	— — — — —	●
Alternative 7: Clay County Minimum with Path & Southern Alignment Shift	— — — — —	●

Construction Costs	Highest Costs Little to No Benefit	Lowest Costs Greatest Benefit
Alternative 1: No Build	— — — — —	●
Alternative 2: Rural Minimum Industry Standards	— — — — —	●
Alternative 3: Rural Minimum Industry Standards with Path	— — — — ●	
Alternative 4: Clay County Minimum	— — — ●	
Alternative 5: Clay County Minimum with Path	— — ●	
Alternative 6: Clay County Minimum with Southern Alignment Shift	— ●	
Alternative 7: Clay County Minimum with Path & Southern Alignment Shift	●	



# Public Input Meeting

- 16 in person attendees
- 60 surveys completed
- Mailed post cards
- Social media posts
- Fargo Forum/FM Extra legal ads
- Press release to media

**15<sup>th</sup> Ave N**  
Corridor Study



**METROCOG**  
15<sup>th</sup> Ave N  
Corridor Study

The Fargo-Moorhead Metropolitan Council of Governments (Metro COG) is hosting an Open House to gather input on corridor alternatives for 15th Ave N in Dilworth between Clay County Highway 9 (40th Street North) and Clay County Highway 11 (70th Street North).

**OPEN HOUSE**

**When:**  
Thursday, November 21  
5 pm - 7 pm

**Where:**  
Dilworth City Depot  
3 4th Street NE, Dilworth, MN

 Can't make the meeting? Head over to the project website to learn more.

[fmmetrocog.org/15th-avenue-n-corridor-study-home](http://fmmetrocog.org/15th-avenue-n-corridor-study-home)

**KLJ Engineering**  
Sponsored

Now is the time to provide feedback on options for 15th Ave N in Dilworth. Take the short survey now!

**15<sup>th</sup> Ave N**  
Corridor Study

**What alternative would you like to see on 15th Ave N in Dilworth?**

**Take the short survey now. >>**

[fmmetrocog.org/15th-Ave-N-Survey](http://fmmetrocog.org/15th-Ave-N-Survey) [Learn more](#)

4


Like Comment Share

**OG**  
ANIZATION




# Public Input Meeting

Question 1: Please rank the following metrics in order from most important to least important.





# Public Input Meeting



**15<sup>th</sup> Ave N**  
Corridor Study

**What alternative would you like to see implemented on 15th Ave N?**

**Vote for your favorite**

**No Build (Typical Section 1)**

**Rural Minimum Industry Standard (Typical Section 2)**

**Rural Minimum Industry Standard with Path (Typical Section 3)**

**Clay County Minimum (Typical Section 4)**

**Clay County Minimum with Path (Typical Section 5)**

**Clay County Minimum with Southern Alignment Shift (Typical Section 6)**


**Clay County Minimum with Southern Alignment Shift and Path (Typical Section 7)**

**METROCOG** **15<sup>th</sup> Ave N Corridor Study** **Engineering Reimagined** **KLJ**



# Public Input Meeting


Question 3: Where do you live?





# Implementation Plan

- **Memorandum of Understanding**
  - Forum for corridor preservation
  - Regular communication
  - Cost sharing
- **Timing / Phasing**
  - East to west
  - Fully paved by 2030





# Implementation Plan

- **Ownership**
  - County
  - Cost sharing via MOU
- **Local Funding**
  - Identify cost shares in an MOU
- **State Funding**
  - Local Road Improvement Program (LRIP)
    - Fall 2025 (Next Solicitation)



# Implementation Plan

- **Functional Classification**
  - Key to Federal Funding
- **Federal Funds**
  - Surface Transportation Block Grant Program (STPBG)
    - Through Metro COG
  - Carbon Reduction Program
    - Linking to TH 10 relief/congestion
  - Competitive/Discretionary Programs
    - Not a good fit for this corridor



# Next Steps

- KLJ to finalize Corridor Study Report
- Presentations to Dilworth, Clay County, Metro COG